

## PU Sealing Compound Primer 379

Adhesion promoter for use with Brillux PU Sealing Compound 382  
and Hybrid Sealing Compound 383



### Field of application

Universal primer to promote the adhesion of PU Sealing Compound 382 and Hybrid Sealing Compound 383 on concrete, aerated concrete, brickwork, plaster, fiber cement, and some metals, as well as plastic materials.

### Properties

- Special universal primer
- Promotes the adhesion of PU Sealing Compound 382 and Hybrid Sealing Compound 383
- For interior and exterior use

### Material description

<b>Color shade</b>	Yellowish, transparent
<b>Base material</b>	Polyurethane
<b>Flash point</b>	-4 °C
<b>Density</b>	Approx. 1.0 g/cm <sup>3</sup>
<b>Packaging</b>	1000 g container

### Use

- Substrate preparation** The substrate must be solid, dry, clean, load-bearing and free from separating agents and dust. Completely remove non-load-bearing layers.
- Application** Keep the container closed until use and do not apply PU Sealing Compound Primer 379 from the original packaging. Only decant as much material as you can apply within a maximum of 30 minutes. Apply PU Sealing Compound Primer 379 undiluted using a paintbrush on the joint edges to create a complete film. Allow the primer to fully flash off prior to applying the Sealing.

## Use

<b>Compatibility</b>	Do not mix with other types of materials.
<b>Consumption</b>	Approx. 100 ml/m <sup>2</sup> depending on the absorption behavior of the substrate. Determine the exact consumption by means of a test application on the object to be coated.
<b>Application temperature</b>	Do not apply under +5 °C and up to a max. of +30 °C object temperature. Do not apply in extremely high humidity, e.g. fog.
<b>Tool cleaning</b>	Clean tools immediately after use with Special Synthetic Resin Thinner 915 or Quick-acting Brush Cleaner 111.

## Drying (+20°C, 65% relative humidity)

After 1 hour flash-off time at the earliest, at the latest after 6 hours, apply PU Sealing Compound 382 to the joint.

## Storage

Store in a cool, dry and frost-free place. Suitable for storage in unopened container for approx. 9 months. Reseal opened containers tightly.

## Declaration

<b>Product code</b>	Not assigned Comply with the specifications in the current safety data sheet.
---------------------	--

## Notes

<b>Further information</b>	Follow the instructions in the data sheets of the products used.
----------------------------	--

## Remark

This Data Sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.

When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.

Brillux  
Weseler Straße 401  
48163 Münster  
GERMANY  
Phone +49 251 7188-0  
Fax +49 251 7188-105  
info@brillux.de  
www.brillux.com