

## PUR Thinner 617

for thinning 2K-PUR-Acryl enamel paints



### Field of Application

Specially designed for consistency regulation of 2K-PUR-Acryl High Gloss Enamel 5740 and 2K-PUR-Acryl Silk Gloss Enamel 5741 for optimal setting to spray viscosity. Also suitable for cleaning the required tools.

### Properties

Intense-acting solvent for thinning 2K-PUR-Acryl enamel paints.

### Material description

<b>Color</b>	colorless
<b>Base material</b>	Solvent mixture based on esters.
<b>VOC value</b>	max. 980 g/l
<b>Flash point</b>	+45°C
<b>Density</b>	Approx. 0.96–0.98 g/cm <sup>3</sup>
<b>Packaging</b>	1 l and 5 l

### Use

Add the relevant product in the specified mixing ratio depending on the individual requirements and mix thoroughly. Follow the more detailed instructions on the viscosity setting in the individual data sheets.

### Storage

Store in a cool and dry place. Protect from direct sunlight. Reseal opened containers tightly.

## Declaration

**Product code** M-VM04  
Comply with the specifications in the current Safety Data Sheet.

## Notes

**Mask surfaces** Carefully mask the surrounding area and particularly sensitive materials.

**Further information** Follow the instructions on the data sheets of the products used.

## Remark

This Data Sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.

When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.

Brillux  
Weseler Straße 401  
48163 Münster  
GERMANY  
Phone +49 251 7188-0  
Fax +49 251 7188-105  
info@brillux.de  
www.brillux.com