

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG
www.brillux.de

Street : Weseler Straße 401

Postal code/City : D - 48163 Münster

Telephone : +49 (0)251-7188-0

Telefax : +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)
Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Corrosion (GHS05)

Signal word

Danger

Hazard components for labelling

POLYDIMETHYLSILOXANE WITH GROUPS OF AMINOALKYLE ; CAS No. : 67923-07-3

ACETIC ACID 7 % ; CAS No. : 64-19-7

Hazard statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

H226 Flammable liquid and vapour.
H318 Causes serious eye damage.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P310 Immediately call a POISON CENTER or a doctor.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container to approved disposal company or local collection.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Impregnating agent based on an alkyl silicon resin.

Hazardous ingredients

POLYDIMETHYLSILOXANE WITH GROUPS OF AMINOALKYLE ; CAS No. : 67923-07-3

Weight fraction : $\geq 20 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315

TETRAETHYL SILICATE ; REACH No. : 01-2119496195-28 ; EC No. : 201-083-8 ; CAS No. : 78-10-4

Weight fraction : $\geq 10 - < 15$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

ACETIC ACID ; REACH No. : 01-2119475328-30 ; EC No. : 200-580-7 ; CAS No. : 64-19-7

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Met. Corr. 1 ; H290 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318 Skin Corr. 1A ; H314: C ≥ 90 % • Eye Dam. 1 ; H318: C ≥ 25 % • Skin Corr. 1B ; H314: C ≥ 25 % • Skin Corr. 1C ; H314: C ≥ 25 % • Eye Irrit. 2 ; H319: C ≥ 10 % • Skin Irrit. 2 ; H315: C ≥ 10 %

METHANOL ; REACH No. : 01-2119433307-44 ; EC No. : 200-659-6 ; CAS No. : 67-56-1

Weight fraction : $\geq 0,3 - < 0,6$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Acute Tox. 3 ; H331 STOT SE 1 ; H370
Specific Conc. Limits : STOT SE 1 ; H370: C ≥ 10 % • STOT SE 2 ; H371: C ≥ 3 %

OCTAMETHYLCYCLOTETRA-SILOXANE ; REACH No. : 01-2119529238-36 ; EC No. : 209-136-7 ; CAS No. : 556-67-2

Weight fraction : $\geq 0,1 - < 0,3$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Repr. 2 ; H361f Aquatic Chronic 1 ; H410
Specific Conc. Limits : (M=10)

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

OCTAMETHYLCYCLOTETRA-SILOXANE ; REACH No. : 01-2119529238-36 ; EC No. : 209-136-7 ; CAS No. : 556-67-2

This mixture contains the following substance of very high concern (SVHC) which is included in the Candidate List according to Article 59 of REACH: Octamethylcyclotetrasiloxane.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand. Persons should be got to safety. Taking self-protection of the first helper into account

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation, eye irritation and irritation to respiratory tract are possible.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO₂, powders or water spray for extinction.

Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Dangerous combustion gases: Nitrogenous gases.

5.3 Advice for firefighters

Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Keeping unprotected persons away. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Avoid contact with eyes and skin. Breathe in avoid of fogs and steams. Paying attention to danger of skidding by product running out/spilled.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly. Disposal into as instructed labelled container.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomite, acid-binders, universal binders, sawdust). Dispose of contaminated material as waste according to section 13. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

Other information

Remove ignition sources.

6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8, information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use. Use only outdoors or in a well-ventilated area.

Measures to prevent fire

Methanol can the product split off. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-valve. Keep away from ignition sources - No smoking. Take precautionary measures against static discharge.

Measures to prevent aerosol and dust generation

Prevent formation of aerosols.

Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container. in a well-ventilated place. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep out of the reach of children.

Hints on joint storage

Store away from foodstuffs. Do not store together with acids.

Storage class (TRGS 510) : 3

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): M-GF01.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

TETRAETHYL SILICATE ; CAS No. : 78-10-4

Limit value type (country of origin) : MAK - Grenzwerte in der Luft am Arbeitsplatz (D)

Limit value : 10 ppm / 86 mg/m³

Version :

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 1,4 ppm / 12 mg/m³

Peak limitation : 1(I)

Version : 02.07.2021

ACETIC ACID ; CAS No. : 64-19-7

Limit value type (country of origin) : MAK - Grenzwerte in der Luft am Arbeitsplatz (D)

Limit value : 10 ppm / 25 mg/m³

Version :

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 10 ppm / 25 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 02.07.2021

ETHANOL ; CAS No. : 64-17-5

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 200 ppm / 380 mg/m³

Peak limitation : 4(II)

Remark : Y

Version : 02.07.2021

METHANOL ; CAS No. : 67-56-1

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 100 ppm / 130 mg/m³

Peak limitation : 2(II)

Remark : H, Y

Version : 02.07.2021

Remark

Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

Biological limit values

METHANOL ; CAS No. : 67-56-1

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Methanol / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts

Limit value : 15 mg/l

Version : 04.05.2021

DNEL-/PNEC-values

DNEL/DMEL

TETRAETHYL SILICATE ; CAS No. : 78-10-4

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

Exposure frequency : Short-term
Limit value : 25 mg/m³
Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 25 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 8,4 mg/kg
Assessment factor : 1 D
Limit value type : DNEL Consumer (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 8,4 mg/kg
Assessment factor : 1 D
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 25 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 25 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 85 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 85 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 12,1 mg/kg
Assessment factor : 1 D
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 12,1 mg/kg
Assessment factor : 1 D
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 85 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 85 mg/m³

PNEC

TETRAETHYL SILICATE ; CAS No. : 78-10-4
Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,192 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

Limit value type : PNEC Intermittierende Einleitung
Exposure route : Water (Including sewage plant)
Limit value : 10 mg/l
Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 0,0192 mg/l
Limit value type : PNEC (Sediment, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,18 mg/kg
Limit value type : PNEC (Sediment, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 0,018 mg/kg
Limit value type : PNEC soil
Exposure route : Soil
Limit value : 0,05 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 4000 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use safety glasses. Having eye rinsing bottle at work ready.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 60 min.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

At use as agreed: Not required. Using at aerosol or fog respiratory protection. Use suitable respiratory protective device in case of insufficient ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Breathing protection equipment required in inadequately ventilated places (gas mask ABEK).

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not inhale gases / fumes / aerosols.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

Appearance

Physical state : Liquid.

Colour : conformable to product designation.

Odour

Poor, characteristic.

Safety characteristics

Melting point/freezing point :	(1013 hPa)		No data available
Initial boiling point and boiling range :	(1013 hPa)		No data available
Decomposition temperature :	(1013 hPa)		No data available
Flash point :		25	°C
Auto-ignition temperature :		310	°C
Lower explosion limit :			No data available
Upper explosion limit :			No data available
Vapour pressure:	(20 °C)		no data available
Density :	(20 °C)	approx.	0,95 - 0,97 g/cm ³
Solvent separation test :	(20 °C)	<	3 %
Water solubility :	(20 °C)		mixable
pH value :	(20 °C / 500 g/l)		5 - 6
log P O/W :			No data available
Flow time :	(20 °C)		No data available
Viscosity :	(20 °C)		1 - 10 mPa*s
Kinematic viscosity :	(40 °C)		No data available
Relative vapour density :	(20 °C)		No data available
Flammable liquids :			The product is ignitable.
Particle Characteristics :			not applicable

9.2 Other information

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.
Avoid moisture.

10.5 Incompatible materials

No dangerous reaction known. Formation of methanol by reaction with acids, lyes, moisture possible.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. By humidity, water and protables means: Methanol and ethanol. Applies to the silicone amount existing in the substance: Measuring at temperatures as of ca. 150 ° degrees Celsius has arisen that lot of formaldehyde is split off one low by an oxidative reduction.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter : LC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Exposure route : Oral
Species : Rat
Effective dose : > 2500 mg/kg

Parameter : LD50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route : Oral
Species : Rat
Effective dose : 3310 mg/kg

Parameter : LD50 (METHANOL ; CAS No. : 67-56-1)
Exposure route : Oral
Species : Rat
Effective dose : 5628 mg/kg

Acute dermal toxicity

Parameter : LD50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route : Dermal
Species : Rabbit
Effective dose : 1060 mg/kg

Parameter : LD50 (METHANOL ; CAS No. : 67-56-1)
Exposure route : Dermal
Species : Rabbit
Effective dose : 15,8 g/kg

Acute inhalation toxicity

Parameter : LC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Exposure route : Inhalation (dust/mist)
Species : Rat
Effective dose : 10 mg/l
Exposure time : 4 h

Parameter : LC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Exposure route : Inhalation (vapour)
Species : Mouse
Effective dose : > 0,85 mg/l
Exposure time : 4 h

Parameter : LC50 (ACETIC ACID ; CAS No. : 64-19-7)
Exposure route : Inhalation
Species : Mouse
Effective dose : 5620 mg/l

Parameter : LC50 (METHANOL ; CAS No. : 67-56-1)
Exposure route : Inhalation
Species : Practical experience/human evidence
Effective dose : 64 g/kg

Corrosion

Irritation:

- Skin contact: No damage or irritation can be expected due to test results of a product with a similar composition.
- Eye contact: Causes serious eye damage.

Respiratory or skin sensitisation

A sensitizing effect by the product is not known.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

No risk expected.

STOT-repeated exposure

No risk expected.

Aspiration hazard

No risk expected.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Species : Danio rerio (zebrafish)
Effective dose : > 245 mg/l

Acute (short-term) toxicity to crustacea

Parameter : EC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Species : Daphnia magna (Big water flea)
Effective dose : > 75 mg/l

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Species : Pseudokirchneriella subcapitata
Effective dose : > 100 mg/l
Exposure time : 72 h

Sewage treatment plant

Parameter : EC50 (TETRAETHYL SILICATE ; CAS No. : 78-10-4)
Inoculum : Activated sludge
Effective dose : > 100 mg/l
Exposure time : 3 h

12.2 Persistence and degradability

By hydrolysis: Ethanol, methanol and silanole and/or Siloxanol connections. The hydrolysis product (methanol) is biologically easily degradable. The hydrolysis product (ethanol) is biologically easily degradable.

12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not data available about the potential of the product concerning his mobility in the ground. A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

The mixture contains the following substances fulfilling the PBT-/vPvB criteria according to REACH Annex XIII

- **PBT :**
OCTAMETHYLCYCLOTETRAILOXANE ; CAS No. : 556-67-2
- **vPvB :**
OCTAMETHYLCYCLOTETRAILOXANE ; CAS No. : 556-67-2

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations.

Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

Waste codes/waste designations according to EWC/AVV

For the product:

Disposal-definition No.: 08 01 11* - Paint and varnish waste which contains organic solvents or other dangerous substances.

After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Disposal-definition No.: 15 01 10 * packings which contain dangerous substances or are polluted by dangerous substances.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TRIMETHOXY(2,4,4-TRIMETHYLPENTYL)SILAN · TETRAETHYL SILICATE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (TRIMETHOXY(2,4,4-TRIMETHYLPENTYL)SILAN · TETRAETHYL SILICATE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (TRIMETHOXY(2,4,4-TRIMETHYLPENTYL)SILAN · TETRAETHYL SILICATE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512
Revision date : 08.12.2022
Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

Tunnel restriction code : D/E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3
Sea transport (IMDG)
Class(es) : 3.3
Hazard label(s) : 3
Air transport (ICAO-TI / IATA-DGR)
Class(es) : 3
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

National regulations

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Additional information

The product is not classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils not the criteria for solid substances according to the TRwS 779 number 2.1.1.

Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

ATEmix: Calculated acute toxicity estimate of mixture
BCF: Bio-Concentration Factor
CAS: Chemical Abstract Service
CLP: Classification, Labelling and Packaging
CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction
CSR: Chemical Safety Report
DNEL: Derived No Effect Level
EC: European Commission
EC50: Effective Concentration 50%
ECHA: European Chemical Agency
EEC: European Economic Community
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EWC: European Waste Catalogue
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IC50: Inhibition Concentration 50%
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Lethal concentration 50%
LD50: Lethal Dose 50%
LOAEL: Lowest Observed Adverse Effect Level
LOEL: Lowest observable effect level
MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)
MARPOL: Convention for the Prevention of Marine Pollution from Ships
MVZ: molar ratio
n.a.: Not applicable
n.d.: Not determined
n.r.: Not relevant
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OEL: Occupational Exposure Limit
PBT: Persistent, bioaccumulative, toxic
PNEC: Predicted No Effect Concentration
RCP: Reciprocal calculation procedure
REACH: Registration, Evaluation and Authorization of Chemical
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
SVHC: Substance of Very High Concern
TLV - TWA: Threshold Limit Value - Time Weighed Average
VOC: Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Hydro Facade Impregnating Agent 512
Hydro-Fassadenimprägnierung 512

Revision date : 08.12.2022

Print date : 08.12.2022

Version (Revision) : 11.0.0 (10.0.0)

H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H410	Very toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
