

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 9

SDS No.: 238985

V002.1 Revision: 03.10.2017

printing date: 01.02.2019

Replaces version from: 29.05.2015

Pattex Montage

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Montage

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Assembly adhesive, dispersion

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains preservative(s): Isothiazolinone mixture 3:1 (CIT/MIT). May produce an

allergic reaction.

Precautionary statement: P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

MSDS-No.: 238985 Pattex Montage Page 2 of 9

V002.1

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

1-Component assembly adhesive

Base substances of preparation:

Styrene-acrylate copolymer

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Isothiazolinone mixture 3:1 (CIT/MIT)		0,0001 - < 0,0015	Acute Tox. 2
55965-84-9		%	H330
		(1 ppm- < 15 ppm)	Acute Tox. 3
			H301
			Acute Tox. 2
			H310
			Skin Corr. 1B
			H314
			Skin Sens. 1A
			H317
			Aquatic Acute 1
			H400
			Aquatic Chronic 1
			H410
			M factor (Acute Aquat Tox): 100 M factor
			(Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

MSDS-No.: 238985 Pattex Montage Page 3 of 9

V002.1

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Store in a cool, dry place.

Temperatures between 0 °C and + 30 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Assembly adhesive, dispersion

MSDS-No.: 238985 Pattex Montage Page 4 of 9

V002.1

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

MSDS-No.: 238985 Pattex Montage Page 5 of 9

V002.1

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance paste

liquid white

Odor typical

Odour threshold No data available / Not applicable

pH 7,8 - 9,8

(20 °C (68 °F))

Melting point No data available / Not applicable Solidification temperature No data available / Not applicable

Initial boiling point 100 °C (212 °F) Flash point Not applicable

Evaporation rate

No data available / Not applicable
Flammability

No data available / Not applicable
Explosive limits

No data available / Not applicable
Vapour pressure

No data available / Not applicable
Relative vapour density:

No data available / Not applicable

Density 1,29 - 1,40 g/cm3

(20 °C (68 °F))

Bulk density No data available / Not applicable Solubility No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Partition coefficient: n-octanol/water
Auto-ignition temperature
Decomposition temperature
Viscosity
Viscosity
Viscosity
Viscosity
Viscosity
No data available / Not applicable
No data available / Not applicable
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable
Oxidising properties
No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with acids: production of heat and carbon dioxide.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

MSDS-No.: 238985 Pattex Montage Page 6 of 9

V002.1

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Sensitizing:

An allergic reaction cannot be excluded after repeated skin contact.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Isothiazolinone mixture	LD50	53 mg/kg	oral		rat	not specified
3:1 (CIT/MIT)						_
55965-84-9						

Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Isothiazolinone mixture	LC50	0,171 mg/l	aerosol	4 h	rat	OECD Guideline 403 (Acute
3:1 (CIT/MIT)						Inhalation Toxicity)
55965-84-9						-

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Isothiazolinone mixture	LD50	87,12 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute
3:1 (CIT/MIT)						Dermal Toxicity)
55965-84-9						-

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Isothiazolinone mixture 3:1 (CIT/MIT)	corrosive			not specified
55965-84-9				

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Isothiazolinone mixture	Sensitizing		guinea pig	not specified
3:1 (CIT/MIT) 55965-84-9				

SECTION 12: Ecological information

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following. Do not empty into drains / surface water / ground water.

MSDS-No.: 238985 Pattex Montage Page 7 of 9

V002.1

12.1. Toxicity

Hazardous components	Value	Value	Acute	Exposure	Species	Method
CAS-No.	type		Toxicity	time		
			Study			
Isothiazolinone mixture 3:1	LC50	0,22 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
(CIT/MIT)						203 (Fish, Acute
55965-84-9						Toxicity Test)
	NOEC	0,098 mg/l	Fish	28 d	Oncorhynchus mykiss	OECD Guideline
						210 (fish early lite
	lll					stage toxicity test)
Isothiazolinone mixture 3:1	EC50	0,12 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
(CIT/MIT)						202 (Daphnia sp.
55965-84-9						Acute
						Immobilisation
						Test)
Isothiazolinone mixture 3:1	EC50	0,0052 mg/l	Algae	48 h	Skeletonema costatum	OECD Guideline
(CIT/MIT)						201 (Alga, Growth
55965-84-9						Inhibition Test)
	NOEC	0,00064 mg/l	Algae	48 h	Skeletonema costatum	OECD Guideline
						201 (Alga, Growth
						Inhibition Test)
Isothiazolinone mixture 3:1	EC20	0,97 mg/l	Bacteria	3 h	activated sludge	OECD Guideline
(CIT/MIT)						209 (Activated
55965-84-9						Sludge, Respiration
						Inhibition Test)
Isothiazolinone mixture 3:1	NOEC	0,0036 mg/l	chronic	21 d	Daphnia magna	OECD 211
(CIT/MIT)			Daphnia			(Daphnia magna,
55965-84-9						Reproduction Test)

12.2. Persistence and degradability

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
	readily biodegradable	aerobic	> 60 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
Isothiazolinone mixture 3:1		3,6		calculation		QSAR (Quantitative
(CIT/MIT)						Structure Activity
55965-84-9						Relationship)
Isothiazolinone mixture 3:1	-0,71 -				20 °C	OECD Guideline 117
(CIT/MIT)	0,75					(Partition Coefficient (n-
55965-84-9						octanol / water), HPLC
						Method)

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Isothiazolinone mixture 3:1 (CIT/MIT) 55965-84-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

MSDS-No.: 238985 Pattex Montage Page 8 of 9

V002.1

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code 080410

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0 %

(VOCV 814.018 VOC regulation

CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 238985 Pattex Montage Page 9 of 9

V002.1

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.