

La	be	-(	0	ff

Revision date: 17.01.2022

Product code: 134

Page 1 of 9

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Label-Off UFI: WHC0-009S-Q00R-GHFD 1.2. Relevant identified uses of the substance or mixture and uses advised against Uses advised against 1.3. Details of the supplier of the safety data sheet Company name: ITW LLC & Co. KG Street: Am Eichenbach 14 Place: D-73054 Eislingen/Fils 07041/96340 Telephone: e-mail: info@itwcp.de Internet: itwcp.de Responsible Department: Produktsicherheit Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00 Swiss Toxicological Information Centre - Téléphone : +41 44 251 51 51 (in Switzerland dial 145)

	United Kingdom : National Poisons Information Service - Phone number :
	8448920111
	Österreich : Vergiftungsinformationszentrale Vienna - Telefon-Nummer : +43 1 406 43 43
	Schweiz : Tox Info Suisse - Telefon-Nummer : +41 44 251 51 51
	España : Instituto Nacional de Toxicología - Teléfono : +34 91 562 04 20
	România (Romania): Spitalul de Urgenta Floreasca 021 230 8000
1.4. Emergency telephone	Deutschland: ++49(0)7041-96340
nu naha w	

number:

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1 Skin corrosion/irritation: Skin Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C6, Isoalkane, D-Limonen Danger

Signal word:



### Label-Off

Revision date: 17.01.2022

Product code: 134

Page 2 of 9

Pictograms:



### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

· · · · · · · · · · · · · · · · · · ·	
P501	Dispose of contents/container to an appropriate recycling or disposal facility.
P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
	Hydrocarbons, C6, isoalkanes, <5%	% n-hexane		40-70 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE H411	3, Asp. Tox. 1, Aquatic Chr	onic 2; H225 H315 H336 H304	
5989-27-5	(R)-p-mentha-1,8-diene; d-limonen	10-30%		
	227-813-5	601-029-00-7		
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens H400 H410	ic Chronic 1; H226 H315 H317		
927-356-8	Hyrdrocarbons, C9-C11, n-alkane,	10-25%		
			01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox	. 1; H226 H336 H304		
124-38-9	Carbondioxide			2,5-10 %
	204-696-9			
	Compressed gas; H280			
64-17-5	ethanol; ethyl alcohol	<1%		
	200-578-6	603-002-00-5		
	Flam. Liq. 2; H225			

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

### Label-Off

Revision date: 17.01.2022

Product code: 134

Page 3 of 9

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	Limits, M-factors and ATE	
	931-254-9	Hydrocarbons, C6, isoalkanes, <5% n-hexane	40-70 %
	inhalation: L0 mg/kg	c50 = 259354 mg/l (vapours); dermal: LD50 = 3350 mg/kg; oral: LD50 = >36750	
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene; d-limonene	10-30% %
	dermal: LD50	) = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64-17-5	200-578-6	ethanol; ethyl alcohol	<1% %
	inhalation: LC	C50 = 95,6 mg/l (vapours); oral: LD50 = 6200 mg/kg	

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

**General information** 

No data available

#### After inhalation

Provide fresh air.

### After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

#### After ingestion

If swallowed, immediately drink: Water.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder.

#### Unsuitable extinguishing media

Water with tenside additive. Water.

### 5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General measures**

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.



### Label-Off

Revision date: 17.01.2022

Product code: 134

Page 4 of 9

### 6.3. Methods and material for containment and cleaning up

#### Other information

Ventilate affected area.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

#### Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL

#### 8.2. Exposure controls



#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Protective and hygiene measures

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

### Eye/face protection

Tightly sealed safety glasses.

#### Hand protection

EN ISO 374 Tested protective gloves are to be worn: NBR (Nitrile rubber) For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. NBR (Nitrile rubber)

#### Skin protection

Protective clothing:

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.



### Label-Off

Revision date: 17.01.2022

Product code: 134

Page 5 of 9

# SECTION 9: Physical and chemical properties

Physical state:	Aerosol		
Colour:	colourless		
Odour:	characteristic		
Changes in the physical sta	te		
Boiling point or initial boiling   boiling range:	point and	60 °C	
Flash point:		< 0 °C	
Lower explosion limits:		1,2 vol. %	
Upper explosion limits:		7 vol. %	
Auto-ignition temperature:		300 °C	
Vapour pressure: (at 20 °C)		227 hPa	
Vapour pressure: (at 50 °C)		719 hPa	
Density:		0,71 g/cm <sup>3</sup>	

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

No data available

#### 10.3. Possibility of hazardous reactions

No data available

### 10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

### 10.5. Incompatible materials

No data available

### 10.6. Hazardous decomposition products

No data available

### **SECTION 11: Toxicological information**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



according to Regulation (EC) No 1907/2006

### Label-Off

Revision date: 17.01.2022

Product code: 134

Page 6 of 9

#### Acute toxicity

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
	Hydrocarbons, C6, isoal	kanes, <5%	n-hexane					
	oral	LD50 mg/kg	>36750	Rat	OECD	Prüfrichtlinie 401		
	dermal	LD50 mg/kg	3350	Rabbit	OECD	Prüfrichtlinie 402		
	inhalation vapour	LC50 mg/l	259354	Rat	OECD	Prüfrichtlinie 403		
5989-27-5	(R)-p-mentha-1,8-diene;	(R)-p-mentha-1,8-diene; d-limonene						
	oral	LD50 mg/kg	> 5000	Rat	GESTIS			
	dermal	LD50 mg/kg	> 5000	Rabbit	GESTIS			
64-17-5	ethanol; ethyl alcohol							
	oral	LD50 mg/kg	6200	Rat	IUCLID			
	inhalation (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS			

### **SECTION 12: Ecological information**

### 12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
	Hydrocarbons, C6, isoalka	anes, <5% n-	hexane				
	Acute fish toxicity	LC50	>1 mg/l	96 h	Fish		
	Acute algae toxicity	ErC50	30 mg/l	72 h	Alge		
	Acute crustacea toxicity	EC50 mg/l	3,87		Daphnia pulex (water flea)		
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene						
	Acute fish toxicity	LC50	0,7 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 mg/l	0,42	48 h	Daphnia magna		
64-17-5	ethanol; ethyl alcohol						
	Acute crustacea toxicity	EC50 14221 mg/l	9268 -	48 h	Daphnia magna	IUCLID	

### 12.3. Bioaccumulative potential

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene	4,23
64-17-5	ethanol; ethyl alcohol	-0,31

#### **Further information**

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods



according to Regulation (EC) No 1907/2006

### Label-Off

Revision date: 17.01.2022

Product code: 134

Page 7 of 9

### **Disposal recommendations**

Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

#### **SECTION 14: Transport information**

# Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 625
Limited quantity:	1 L
Transport category: Tunnel restriction code:	2 D
Other applicable information (land transp	2
E0	ion)
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Other applicable information (inland wate E0	erways transport)
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
<u>14.4. Packing group:</u>	-



	Label-Off	
Revision date: 17.01.2022	Product code: 134	Page 8 of 9
Hazard label:	2, see SP63	
Special Provisions:	63, 190, 277, 327, 344, 959	
Limited quantity: EmS:	See SP277 F-D, S-U	
Other applicable information (marine tra		
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number:	UN1950	
14.2. UN proper shipping name:	AEROSOLS, flammable	
14.3. Transport hazard class(es):	2.1	
Hazard label:	2.1	
Special Provisions:	A145 A167	
Limited quantity Passenger:	30 kg G	
IATA-packing instructions - Passenger:	203	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	75 kg 203	
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	203 150 kg	
Other applicable information (air transp	· ·	
EO	,	
: Y203		
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Yes	¥

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
Restrictions on use (REACH, annex XVII):	
Entry 28	
2004/42/EC (VOC):	62,5 % (443,75 g/l)
National regulatory information	
Water hazard class (D):	2 - obviously hazardous to water

### **SECTION 16: Other information**

#### Relevant H and EUH statements (number and full text)

H222	Extremely flammable aero	osol.

H225	Highly flammable liquid and vapour.
------	-------------------------------------



according to Regulation (EC) No 1907/2006

Label-Off				
Revision date: 17.01.2022	Product code: 134	Page 9 of 9		
H226	Flammable liquid and vapour.			
H229	Pressurised container: May burst if heated.			
H280	Contains gas under pressure; may explode if heated.			
H304	May be fatal if swallowed and enters airways.			
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H336	May cause drowsiness or dizziness.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting effects.			
H411	Toxic to aquatic life with long lasting effects.			

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)