

2K-Aqua EP Hardener 2374

Special epoxy hardener for 2K-Aqua EP Primer 2373 and 2K-Aqua EP Spray Primer 2375



Field of application

To be mixed with 2K-Aqua EP Primer 2373 and 2K-Aqua EP Spray Primer 2375.

Properties

Special system hardener. The container sizes reflect the mixing ratio.

Material description

Color shade	Yellowish-transparent
Base material	Epoxy resin
Density	Approx. 1.12 g/m ³
Packaging	150 ml of hardener for 600 ml of base material 600 ml of hardener for 2.4 l of base material (Base enamel and hardener are supplied separately)

Use

Mixing	Stir 2K-Aqua EP Primer 2373 or 2K-Aqua EP Spray Primer 2375 thoroughly and evenly before adding the hardener. Mix the base component and hardener in the specified mixing ratio shortly before application. Ensure that the hardener container is completely emptied without residue. Follow the instructions in the 2K-Aqua EP Primer 2373 and 2K-Aqua EP Spray Primer 2375 data sheets.
Compatibility	Can only be mixed with materials specified in this data sheet.
Application temperature	Do not apply at temperatures below +8°C or above a max. of +25°C air, substrate and material temperature. Take the dew point temperature into consideration. Do not apply unless the temperature is at least 3°C above the dew point.

Use	
Tool cleaning	Clean tools with water and wetting agent immediately after use.
Storage	
	Store in a cool, dry and frost-free place. Reseal opened containers tightly.
Declaration	
Product code	RE1 Comply with the specifications in the current safety data sheet.
Notes	
Further information	Follow the instructions in the data sheets of the products used.
Remark	
	<p>This data sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.</p> <p>When a new version of this data sheet with updated information is published, the previous version no longer applies. The current version is available on our website.</p> <p>Brillux Weseler Straße 401 48163 Münster GERMANY Phone +49 251 7188-0 Fax +49 251 7188-105 info@brillux.de www.brillux.com</p>