

## Fix Primer LF 3063

solvent-free, ready for application, for priming in the system under  
Adhesive LF 3064, for interior use



### Field of application

For priming absorbent, filled interior floor surfaces in the system build-up with Adhesive LF 3064 for preparing the gluing of Design Floor 3055.

### Properties

- Solvent-free
- Very low-emission
- Ready for application
- Quick-drying
- Easy to apply
- Residual dust binding
- High yield
- Adhesion promoting
- Can be used on a variety of substrates

### Material description

<b>Color shade</b>	turquoise green
<b>Base material</b>	solvent-free emulsion
<b>Density</b>	approx. 1.0 g/cm <sup>3</sup>
<b>Packaging</b>	2.5 kg

## Use

<b>Thinning</b>	Ready to use, therefore apply unthinned.
<b>Compatibility</b>	Do not mix with other types of materials.
<b>Application</b>	Stir or shake Fix Primer LF 3063 thoroughly before using, and pour into a clean bucket. Apply evenl and finish using with the Short Fiber Paint Roller 1217 and brush. Avoid rolled edges and excess material (puddle formation).
<b>Consumption</b>	Approx. 40 g/m <sup>2</sup> undiluted, depending on the absorbency of the substrate and applicator. Determine exact consumption by means of a test application on the object to be coated.
<b>Application temperature</b>	Do not apply at an air and/or substrate temperature that is below +15 °C or above +30 °C.
<b>Tool cleaning</b>	Clean tools immediately after use with water.

## Drying (+20 °C, 65 % relative humidity)

<b>Flash-off time</b>	On cement-bonded substrates, e.g., Floor Leveling Compound C10 3114, Floor Leveling Compound C15 3116 or Floor Leveling Compound FX 3109, allow a flash-off time of approx. 15–20 minutes. On Floor Leveling Compound CA 3059, allow a flash-off time of approx. 30–60 minutes. Allow for a longer flash-off time if the temperature is lower and/or the humidity is higher.
-----------------------	---

## Storage

Store in a cool and frost-free location above +5 °C. Can be stored in the unopened original container for 12 months.  
Reseal opened containers tightly and apply as soon as possible.

## Declaration

<b>Product code</b>	D1 Comply with the specifications in the current Safety Data Sheet.
---------------------	--

## Gluing

### Substrate preparation

The substrate must be solid, dry, clean, load-bearing, and free from efflorescences, sinter layers, and separating agents.  
The floor surfaces must be smoothly filled with suitable Floor Leveling Compounds.  
See also VOB Part C, DIN 18365, Floor Covering Work.  
The substrate conditions must be matched to the requirements for Design Floor 3055.

### Floor covering gluing

Take the flash-off time into consideration while gluing Design Floor Covering 3055 with Adhesive LF 3064.

## Notes

### Specifications of Design Floor Covering 3055

During use and application, the product information and laying instructions for Design Floor Covering 3055 should be followed.

### Comply with the "BEB" data sheets

Comply with the information in the data sheets of the Federal Association of Screeds and Floor Coverings, Troisdorf (BEB), "Evaluating and Preparing Substrates" and "Preparation for Laying Surface Coverings".

### Further information

Follow the instructions in the data sheets of the products used.

## Remark

This Data Sheet is based on extensive development work and years of practical experience. The translation corresponds to the current German version, in compliance with the German laws, regulations, standards and guidelines. Its content does not constitute a contractual legal relationship. The user/buyer is not released from the responsibility of checking our products to ensure they are suitable for the intended application. In addition, our general terms of business apply.

When a new version of this Data Sheet with updated information is published, the previous version no longer applies. The current version is available on our website.

Brillux  
Weseler Straße 401  
48163 Münster  
GERMANY  
Phone +49 251 7188-0  
Fax +49 251 7188-105  
info@brillux.de  
www.brillux.com