

Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Nonwoven Adhesive ELF 375 Vlieskleber ELF 375

- **1.2** Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses
 - Products Category [PC]

PC 1 - Adhesives, sealants

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG www.brillux.de

Street : Weseler Straße 401

Postal code/City: D - 48163 Münster

Telephone : +49 (0)251-7188-0

Telefax : +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.): (Giftinformationszentrum-Nord, Göttingen, consultation in german or english language) Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



Exclamation mark (GHS07) Signal word Warning Hazard components for labelling 1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5 2-METHYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 2682-20-4 Hazard statements

H317 May cause an allergic skin reaction.

Page : 1 / 12



Trade name :	Nonwoven Adhesive ELF 375 Vlieskleber ELF 375		
Revision date :	25.04.2024	Version (Revision) :	7.0.0 (6.1.0)
Print date :	25.04.2024		

Precautionary statements

P102	Keep out of reach of children.
P261	Avoid breathing spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501	Dispose of contents/container to approved disposal company or local collection.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Dispersion adhesive, solvent- and plasticizer-free;

Composition:

Vinylacetate-ethylene-copolymer-dispersion, inorganic pigments, water, additives and preservatives (methyl- and benzisothiazolinone).

Hazardous ingredients

2-METHYL-2H-ISOTHIAZOL-3-ONE ; EC No. : 220-239-6; CAS No. : 2682-20-4

Weight fraction :	≥ 0,0015 - < 0,025 %
Classification 1272/2008 [CLP] :	Acute Tox. 2 ; H330 Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Skin Sens. 1A ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410
Specific Conc. Limits :	Skin Sens. 1A ; H317: C ≥ 0,0015 % • (M Chronic=1) • (M Acute=10)
1,2-BENZISOTHIAZOL-3(2H)-ONE ; R	EACH No. : 01-2120761540-60 ; EC No. : 220-120-9; CAS No. : 2634-33-5
Weight fraction :	≥ 0,005 - < 0,05 %
Classification 1272/2008 [CLP] :	Acute Tox. 2 ; H330 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 2 ; H411
Specific Conc. Limits :	Skin Sens. 1 ; H317: C ≥ 0,05 % • (M Acute=1)

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. If unconscious no administration by mouth, storage in recovery position and seek medical advice. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

adivce if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed Allergic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

This product is not flammable. In case of a fire extingnish surroundings as indicated.

Unsuitable extinguishing media

None known.

5.2 Special hazards arising from the substance or mixture Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. The product produced in combination with water slippery surfaces.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove residue by rinsing thoroughly with water. Thoroughly clean contaminated objects and floors and observe environmental regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. You find information about the safety equipment of persons in the section 8, information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Protective measures

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and

Page : 3 / 12



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

working area. For personal protection see Section 8. Keep out of reach of children. Read label before use.

Measures to prevent fire

This product is not flammable. Cool endangered containers with water.

Advices on general occupational hygiene

While working do not eat , drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Do not store the product in lounge room. Keep only in the original container. Protect against frost. Keep out of the reach of children.

Hints on joint storage

Store away from foodstuffs.

Storage class (TRGS 510): 12

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry - GISCODE): D 1.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL-/PNEC-values

Exposure route :

DNEL/DMEL

,	
1,2-BENZISOTHIAZOL-3(2H)-ONE ; C	AS No. : 2634-33-5
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	1,2 mg/m ³
Limit value type :	DNEL Consumer (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	345 µg/kg bw/day
Limit value type :	DMEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	6,81 mg/m ³
Limit value type :	DMEL worker (systemic)
Exposure route :	Dermal
Exposure frequency :	Long-term
Limit value :	966 µg/kg bw/day
PNEC	
1,2-BENZISOTHIAZOL-3(2H)-ONE ; C	AS No. : 2634-33-5
Limit value type :	PNEC (Aquatic, freshwater)
Exposure route :	Water (Including sewage plant)
Exposure time :	Short-term
Limit value :	4,03 µg/l
Limit value type :	PNEC (Aquatic, intermittent release)

Water (Including sewage plant)



Trade name :

Revision date : Print date :

Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

Exposure time :	Short-term
Limit value :	1,1 μg/l
Limit value type :	PNEC (Aquatic, marine water)
Exposure route :	Water (Including sewage plant)
Exposure time :	Short-term
Limit value :	403 ng/L
Limit value type :	PNEC (Aquatic, marine water)
Exposure route :	Water (Including sewage plant)
Exposure time :	Long-term
Limit value :	110 ng/L
Limit value type :	PNEC Soil, Freshwater
Exposure route :	Soil
Exposure time :	Short-term
Limit value :	49,9 µg/kg dry weight
Limit value type :	PNEC (Soil)
Exposure route :	Soil
Exposure time :	Short-term
Limit value :	3 mg/kg dry weight
Limit value type :	PNEC Soil, Marine water
Exposure route :	Soil
Exposure time :	Short-term
Limit value :	4,99 µg/kg dry weight
Limit value type :	PNEC (Sewage treatment plant)
Exposure route :	Water (Including sewage plant)
Exposure time :	Short-term
Limit value :	1,03 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this shoud be achieved by the use of local exhaust ventilation and good general extraction.

Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use protection glasses in case of spattering.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing. If the product must sprayed, use a disposable protective suit.

Respiratory protection

Breathing protection equipment is not necessary by brush or roll application of the Product in good ventilated rooms. By spraying: Use the combination filter mask A2/P2. Do not breathe gas or spray.

General information

Avoid contact with eves and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe gas or spray.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : conformable to product designation.

Odour

Characteristic.

Safety characteristics

Melting point/freezing point :	(1013 hPa)		No data available		
Initial boiling point and boiling range :	(1013 hPa)	>	100	°C	
Decomposition temperature :	(1013 hPa)		No data available		
Flash point :			not applicable		
Auto-ignition temperature :			not applicable		
Vapour pressure :	(50 °C)		No data available		
Density :	(20 °C)	approx.	0,99 - 1,03	g/cm ³	
Solvent separation test :	(20 °C)		not applicable		
pH :			8 - 9		
log P O/W :			No data available		
Flow time :	(20 °C)		No data available		DIN-cup 4 mm
Viscosity :	(20 °C)		thixotropic		
Kinematic viscosity :	(40 °C)		No data available		
Relative vapour density :	(20 °C)		No data available		
VOC-value :		max.	1	g/l	
Flammable liquids :	The product is not i	gnitable.			
Particle Characterics :	not applicable				

9.2 Other information

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No dangerous reactions are known if stored and handled the product correctly.

10.4 Conditions to avoid

Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Acute toxicity: - Acute oral toxicity: No data available; - Acute dermal toxicity: No data available; - Acute inhalation toxicity: No data available. Acute oral toxicity Parameter : ATEmix calculated Exposure route : Oral Effective dose : not relevant Parameter : LD50 (2-METHYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 2682-20-4) Exposure route : Oral Species : Rat Effective dose : 285 mg/kg Parameter : LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5) Exposure route : Oral Species : Rat 597 mg/kg Effective dose : Acute dermal toxicity Parameter : ATEmix calculated Exposure route : Dermal Effective dose : not relevant Parameter : LD50 (2-METHYL-2H-ISOTHIAZOL-3-ONE; CAS No.: 2682-20-4) Exposure route : Dermal Species : Rat Effective dose : > 2000 mg/kg Parameter : LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5) Exposure route : Dermal Species : Rat Effective dose : > 2000 mg/kg Acute inhalation toxicity ATEmix calculated Parameter : Exposure route : Inhalation (vapour) Effective dose : not relevant Parameter : LC50 (2-METHYL-2H-ISOTHIAZOL-3-ONE ; CAS No. : 2682-20-4) Exposure route : Inhalation Species : Rat Effective dose : 0,38 mg/l Exposure time : 4 h Corrosion - To the skin: Not expecting any damage or irritancy.

- At the eye: Not expecting any damage or irritancy.

Respiratory or skin sensitisation

The product is labeled as skin sensitizing.

Skin sensitisation

Parameter :Skin sensitisation (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)Species :MouseResult :Sensitising.Method :OECD 429

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

Page : 7 / 12



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

No risk expected.

STOT-repeated exposure

No risk expected.

Aspiration hazard

No risk expected.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regualtion), listed in sections 2 and 3. At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Chronic (long-term) fish toxicit	у
Parameter :	NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Species :	Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter :	Chronic (long-term) fish toxicity
Effective dose :	0,21 mg/l
Exposure time :	28 D
Method :	OECD 215
Chronic (long-term) toxicity to	aquatic invertebrate
Parameter :	NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Species :	Daphnia magna (Big water flea)
Evaluation parameter :	Chronic (long-term) daphnia toxicity
Effective dose :	1,2 mg/l
Exposure time :	21 D
Method :	OECD 211
Toxicity to other aquatic plants	/organisms
Parameter :	NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Species :	Selenastrum capricornutum
Evaluation parameter :	Acute (short-term) algae toxicity
Effective dose :	0,04 mg/l
Exposure time :	72 h
Sewage treatment plant	
Parameter :	EC20 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Inoculum :	Activated sludge
Evaluation parameter :	Effects in sewage plants
Effective dose :	3,3 mg/l
Exposure time :	3 h
Parameter :	EC50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Inoculum :	Activated sludge
Evaluation parameter :	Effects in sewage plants
Effective dose :	13 mg/l
Exposure time :	3 h



Trade name :

Revision date : Print date :

P

P

Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

Biodegradation

Parameter :	Biodegradation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)
Inoculum :	Degree of elimination
Degradation rate :	approx. 90 %
Evaluation :	Biodegradable.
Method :	OECD 302B
Parameter :	Biodegradation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)
Inoculum :	Degree of elimination
Degradation rate :	> 70 %
Evaluation :	Biodegradable.
Method :	OECD 303A

12.3 Bioaccumulative potential

Parameter :	Bioconcentration factor (BCF) (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)
Value :	6,95
Method :	OECD 305

These are not data availble about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas available about the potential of the product concerning his mobility in the ground. A penetrating into soil, waters and sewage system should be prevented.

Adsorption

•	
Parameter :	Log KOW (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)
Effective dose :	0,7
Evaluation :	HPLC method
Method :	OECD 117

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage. The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

Waste codes/waste designations according to EWC/AVV

For the product:

Code of the European waste catalogue (EWC-Code):

08 01 11* Paint and varnish waste which contains organic solvents or other dangerous substances.

After intended use



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Code of the European waste catalogue (EWC-Code):

15 01 10* - packaging containing residues of or contaminated by hazardous substances.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the Internationa Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions):

Use restriction according to REACH annex XVII, no.: 3, 75

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes. This product contains max. 1 g/l VOC.

National regulations

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Additional information

The product is classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils the criteria for solid substances according to the TRwS 779 number 2.1.1. Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information



7.0.0 (6.1.0)

 Trade name :
 Nonwoven Adhesive ELF 375

 Vieskleber ELF 375
 Version (Revision) :

 Print date :
 25.04.2024

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling \cdot 15. Restrictions on use \cdot 15. Water hazard class

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route) AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany) AOX: Adsorbable Organic halogen compounds ATEmix: Calculated acute toxicity estimate of mixture BCF: Bio-Concentration Factor CAS: Chemical Abstract Service CLP: Classification, Labelling and Packaging CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction CSR: Chemical Safety Report DNEL: Derived No Effect Level EC: European Commission EC50: Effective Concentration 50% ECHA: European Chemical Agency EEC: European Economic Community EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances EWC: European Waste Catalogue GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals IATA: International Air Transport Association ICAO: International Civil Aviation Organization IC50: Inhibition Concentration 50% IMDG Code: International Maritime Dangerous Goods Code IMO: International Maritime Organization LC50: Lethal concentration 50% 1D50: Lethal Dose 50% LOAEL: Lowest Observed Adverse Effect Level LOEL: Lowest observable effect level MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG) MARPOL: Convention for the Preventation of Marine Pollution from Ships MVZ: molar ratio n.a.: Not applicable n.d.: Not determined n.r.: Not relevant NLP: No Longer Polymers NOAEC: No Observed Adverse Effect Concentration NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration NOEL: No Observed Effect Level OEL: Occupational Exposure Limit PBT: Persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RCP: Reciprocal calculation procedure REACH: Registration, Evaluation and Authorization of Chemical) RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer) STEL: Short-term Exposure Limit SVHC: Substance of Very High Concern TLV - TWA: Threshold Limit Value - Time Weighed Average VOC: Volatile Organic Compounds vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data



Trade name :

Revision date : Print date : Nonwoven Adhesive ELF 375 Vlieskleber ELF 375 25.04.2024 25.04.2024

Version (Revision) :

7.0.0 (6.1.0)

Regulation (EC) No. 1907/2006 (REACH), amended by the Regulation (EC) 2020/878 Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixture ADN: (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) ADR: (Accord européen relatif transport des merchandises dangereuses par route) Database of the registered Substances of the European Chemicals Agency (ECHA) GESTIS - Database on hazardous substances - (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance) Information of our suppliers GISBAU (Hazardous materials information system of the German professional associations of the building and construction industry) Classification for mixtures and used evaluation method according to regulation (EC) 16.4 No 1272/2008 [CLP] The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation). 16.5 Relevant H- and EUH-phrases (Number and full text) H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H314 Causes severe skin burns and eve damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H330 Fatal if inhaled.

- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.