according to Regulation (EC) No. 1907/2006 (REACH)



Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Crack Stop Filler 376 Riss-Stop-Spachtel 376

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 1 - Adhesives, sealants

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG www.brillux.de

Street: Weseler Straße 401

Postal code/City: D - 48163 Münster

Telephone: +49 (0)251-7188-0 **Telefax:** +49 (0)251-7188-280 Information contact:

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):

(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)

Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Additional information

This product is not dangerous according to the regulation (EC) No. 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE; REACTION MASS OF: 5-CHLORO-2-METHYL-4-**EUH208**

ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1). May produce an

allergic reaction.

FUH210 Safety data sheet available on request.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

Page: 1 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 **Version (Revision):** 10.0.0 (9.0.0)

Print date : 04.10.2023

3.2 Mixtures

Description

Sealant based on an acrylic copolymer dispersion, extenders, water and auxiliaries.

Hazardous ingredients

1,2-BENZISOTHIAZOL-3(2H)-ONE; REACH No.: 01-2120761540-60; EC No.: 220-120-9; CAS No.: 2634-33-5

Weight fraction : $\geq 0,005 - < 0,05 \%$

Classification 1272/2008 [CLP]: Acute Tox. 2; H330 Eye Dam. 1; H318 Acute Tox. 4; H302 Skin Irrit. 2; H315

Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411

Specific Conc. Limits : Skin Sens. 1 ; H317: C ≥ 0,05 % • (M Acute=1)

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1); EC No.

: 611-341-5; CAS No. : 55965-84-9

Weight fraction: < 0,0015 %

Classification 1272/2008 [CLP]: Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Skin Corr. 1C; H314

Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1

; H410 EUH071

Specific Conc. Limits : Eye Dam. 1; H318: $C \ge 0.6\%$ • Skin Corr. 1C; H314: $C \ge 0.6\%$ • Eye Irrit. 2;

H319: C ≥ 0,06 % • Skin Irrit. 2 ; H315: C ≥ 0,06 % • Skin Sens. 1A ; H317: C ≥

0,0015 % • (M=100)

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. If unconscious no administration by mouth, storage in recovery position and seek medical advice. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical adivce if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Allergic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

This product is not flammable. In case of a fire extingnish surroundings as indicated.

Page: 2 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Crack Stop Filler 376 Trade name:

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

Unsuitable extinguishing media

None known.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. The product produced in combination with water slippery surfaces.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove residue by rinsing thoroughly with water. Thoroughly clean contaminated objects and floors and observe environmental regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8,

information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and working area. For personal protection see Section 8. Keep out of reach of children. Read label before use.

Measures to prevent fire

This product is not flammable. Cool endangered containers with water.

Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Do not store the product in lounge room. Keep only in the original container. Protect against frost. Keep out of the reach of children.

Hints on joint storage

Store away from foodstuffs.

Storage class (TRGS 510): 12

Further information on storage conditions

Page: 3 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE: Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry - GISCODE): D 1.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL-/PNEC-values

DNEL/DMEL

1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5

Limit value type: DNEL Consumer (systemic)

Exposure route: Inhalation Exposure frequency: Long-term Limit value: 1,2 mg/m³

Limit value type: **DNEL Consumer (systemic)**

Exposure route: Dermal Exposure frequency: Long-term 345 µg/kg bw/day Limit value: Limit value type: DMEL worker (systemic)

Exposure route: Inhalation Exposure frequency: Long-term Limit value: 6,81 mg/m³

Limit value type : DMEL worker (systemic)

Exposure route : Dermal Long-term Exposure frequency: Limit value: 966 µg/kg bw/day

PNEC

1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5

PNEC (Aquatic, freshwater) Limit value type: Exposure route: Water (Including sewage plant)

Exposure time: Short-term Limit value : 4,03 µg/l

Limit value type : PNEC (Aquatic, intermittent release) Exposure route: Water (Including sewage plant)

Exposure time: Short-term Limit value : 1,1 µg/l

Limit value type: PNEC (Aquatic, marine water) Exposure route: Water (Including sewage plant)

Exposure time : Short-term Limit value: 403 ng/L

Limit value type: PNEC (Aquatic, marine water) Water (Including sewage plant) Exposure route:

Exposure time: Long-term Limit value: 110 ng/L

Limit value type: PNEC Soil, Freshwater

Exposure route: Soil Exposure time: Short-term

Limit value : 49,9 µg/kg dry weight

Limit value type: PNEC (Soil) Exposure route: Soil

Page: 4 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

> Exposure time: Short-term

Limit value : 3 mg/kg dry weight Limit value type : PNEC Soil, Marine water

Exposure route : Soil Exposure time: Short-term

Limit value: 4,99 µg/kg dry weight

Limit value type : PNEC (Sewage treatment plant) Water (Including sewage plant) Exposure route :

Exposure time : Short-term Limit value: 1,03 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this shoul be achieved by the use of local exhaust ventilation and good general extraction.

Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use protection glasses in case of spattering.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

Breathing protection equipment is not required in adequately ventilated places. Do not inhale the vapour.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Pasty.

Colour: conformable to product designation.

Odour

Poor, characteristic.

Safety characteristics

Melting point/freezing point: (1013 hPa) No data available

Initial boiling point and boiling (1013 hPa) 100 °C > range:

Decomposition temperature: (1013 hPa) No data available

Page: 5 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 **Version (Revision):** 10.0.0 (9.0.0)

Print date : 04.10.2023

Flash point:

Auto-ignition temperature:

Lower explosion limit:

Upper explosion limit:

Not applicable

vapur pressure:

(50 °C)

No data available

Density : ($20 \, ^{\circ}\text{C}$) approx. 1,85 g/cm³ **Solvent separation test :** ($20 \, ^{\circ}\text{C}$) not applicable

Solvent separation test :(20 °C)not applicableWater solubility :(20 °C)mixablepH :No data availablelog P O/W :No data available

Flow time : ($20 \, ^{\circ}\text{C}$) No data available DIN-cup 4 mm

 Viscosity:
 (20 °C)
 pasty

 Kinematic viscosity:
 (40 °C)
 No data available

 Relative vapour density:
 (20 °C)
 No data available

 VOC-value:
 max.
 1

Flammable liquids : The product is not ignitable.

Particle Characterics : not applicable

9.2 Other information

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No dangerous reactions are known if stored and handled the product correctly.

10.4 Conditions to avoid

Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter: LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)

Exposure route: Oral
Species: Rat
Effective dose: 597 mg/kg

Parameter: LC50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

Page: 6 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Crack Stop Filler 376 Trade name:

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Exposure route: Oral Species: Rat 2200 mg/kg Effective dose:

Acute dermal toxicity

Parameter: LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5)

Exposure route: Species: Rat

> 2000 mg/kg Effective dose:

Acute inhalation toxicity

LC50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-Parameter:

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No. : 55965-84-9)

Inhalation Exposure route: Species: Rat Effective dose: 5,7 mg/l 4 h Exposure time:

Corrosion

- To the skin: Not expecting any damage or irritancy.

- At the eye: Not expecting any damage or irritancy.

Respiratory or skin sensitisation

The product contains sensitizing substances, which may produce an allergic reaction (see section 2 and 3).

Skin sensitisation

Parameter: Skin sensitisation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Mouse Result: Sensitising. **OECD 429** Method:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

No risk expected.

STOT-repeated exposure

No risk expected.

Aspiration hazard

No risk expected.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regualtion), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Page: 7 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

> EC50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-Parameter:

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose: 0,22 mg/l Exposure time: 96 h

Chronic (long-term) fish toxicity

Parameter: NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Oncorhynchus mykiss (Rainbow trout) Chronic (long-term) fish toxicity Evaluation parameter:

Effective dose: 0,21 mg/l 28 D Exposure time: Method: **OECD 215**

Parameter: NOEC (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose: 0,098 mg/l 28 D Exposure time: Acute (short-term) toxicity to crustacea

Parameter: EC50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Effective dose: 0,1 mg/l 48 h Exposure time:

Chronic (long-term) toxicity to aquatic invertebrate

Parameter: NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Daphnia magna (Big water flea) Evaluation parameter: Chronic (long-term) daphnia toxicity

Effective dose: 1,2 mg/l Exposure time: 21 D Method: **OECD 211**

Parameter: NOEC (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Effective dose: 0,004 mg/l Exposure time: 21 D

Acute (short-term) toxicity to algae and cyanobacteria

Parameter: EC50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Pseudokirchneriella subcapitata

Effective dose: 0,048 mg/l Exposure time: 72 h

Parameter: EL50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Pseudokirchneriella subcapitata

Effective dose: 0,0012 mg/l Exposure time: 72 h

Parameter: EC50 (REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Algae

Evaluation parameter: Anabaena flos-aquae

Effective dose: 0,043 mg/l Exposure time: 120 h

Toxicity to other aquatic plants/organisms

Parameter: NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Selenastrum capricornutum Evaluation parameter: Acute (short-term) algae toxicity

Effective dose: 0,04 mg/l

Page: 8 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Crack Stop Filler 376 Trade name:

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

> Exposure time: 72 h

Sewage treatment plant

Parameter: EC20 (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Inoculum: Activated sludge Effects in sewage plants Evaluation parameter:

Effective dose: 3,3 mg/l Exposure time:

EC50 (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5) Parameter:

Inoculum: Activated sludge Evaluation parameter: Effects in sewage plants

Effective dose: 13 mg/l Exposure time:

12.2 Persistence and degradability

These are not data avaible about the potential of the product concerning his persistency and degradability.

Biodegradation

Biodegradation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5) Parameter:

Inoculum: Degree of elimination approx. 90 % Degradation rate: Evaluation: Biodegradable. Method: OECD 302B

Parameter: Biodegradation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Inoculum: Degree of elimination

Degradation rate: > 70 % Evaluation: Biodegradable. Method: OECD 303A

12.3 Bioaccumulative potential

Parameter: Bioconcentration factor (BCF) (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Value: 6,95 Method: **OECD 305**

These are not data availble about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas availble about the potential of the product concerning his mobility in the ground.

A penetrating into soil, waters and sewage system should be prevented.

Adsorption

Parameter: Log KOW (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Effective dose: 0,7 HPLC method Evaluation: **OECD 117** Method:

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

Page: 9 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Crack Stop Filler 376 Trade name:

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

Waste codes/waste designations according to EWC/AVV

For the product:

Disposal-definition No.: 08 01 12 - Paint and varnish waste with the exception of the ones who come under 08 01 11 *.

After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the Internationa Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

This product contains max. 1 g/l VOC.

National regulations

Water hazard class

Classification according to AwSV - Class: 1 (Slightly hazardous to water)

Additional information

The product is classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils the criteria for solid substances according to the TRwS 779 number 2.1.1. Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

Page: 10 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 Version (Revision): 10.0.0 (9.0.0)

Print date: 04.10.2023

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report DNEL: Derived No Effect Level EC: European Commission EC50: Effective Concentration 50%

ECHA: European Chemical Agency EEC: European Economic Community

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EWC: European Waste Catalogue

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IC50: Inhibition Concentration 50%

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

LC50: Lethal concentration 50%

LD50: Lethal Dose 50%

LOAEL: Lowest Observed Adverse Effect Level

LOEL: Lowest observable effect level

MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG) MARPOL: Convention for the Preventation of Marine Pollution from Ships

MVZ: molar ratio n.a.: Not applicable n.d.: Not determined n.r.: Not relevant NLP: No Longer Polymers

NOAEC: No Observed Adverse Effect Concentration

NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration

NOEL: No Observed Effect Level OEL: Occupational Exposure Limit PBT: Persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RCP: Reciprocal calculation procedure

REACH: Registration, Evaluation and Authorization of Chemical)

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant

le transport de marchandises dangereuses par chemin de fer)

STEL: Short-term Exposure Limit SVHC: Substance of Very High Concern

TLV - TWA: Threshold Limit Value - Time Weighed Average

Page: 11 / 12

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Crack Stop Filler 376

Riss-Stop-Spachtel 376

Revision date: 04.10.2023 **Version (Revision):** 10.0.0 (9.0.0)

Print date : 04.10.2023

VOC: Volatile Organic Compounds

vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 12 / 12