

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Nitro Thinner 456
Nitro-Verdünnung 456

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG
www.brillux.de

Street : Weseler Straße 401

Postal code/City : D - 48163 Münster

Telephone : +49 (0)251-7188-0

Telefax : +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)
Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)



Flame (GHS02) · Health hazard (GHS08) · Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

REACTION MASS OF ETHYLBENZENE AND XYLENE
N-BUTYL ACETATE ; CAS No. : 123-86-4
BUTAN-1-OL ; CAS No. : 71-36-3
HYDROCARBONS, C9, AROMATICS

Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P273 Avoid release to the environment.
P312 Call a POISON CENTER or a doctor if you feel unwell.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
P331 Do NOT induce vomiting.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container to approved disposal company or local collection.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Solvent mixture based on organic solvents.

Hazardous ingredients

REACTION MASS OF ETHYLBENZENE AND XYLENE ; REACH No. : 01-2119486136-34 ; EC No. : 905-588-0

Weight fraction : $\geq 40 - < 45$ %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4
Weight fraction : $\geq 30 - < 35 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066

BUTAN-1-OL ; REACH No. : 01-2119484630-38 ; EC No. : 200-751-6; CAS No. : 71-36-3
Weight fraction : $\geq 10 - < 15 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 STOT SE 3 ; H336

HYDROCARBONS, C9, AROMATICS ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5
Weight fraction : $\geq 5 - < 10 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 EUH066

ACETONE ; REACH No. : 01-2119471330-49 ; EC No. : 200-662-2; CAS No. : 67-64-1
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066

ETHYL ACETATE ; REACH No. : 01-2119475103-46 ; EC No. : 205-500-4; CAS No. : 141-78-6
Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066

TOLUENE ; EC No. : 203-625-9; CAS No. : 108-88-3
Weight fraction : $\geq 0,5 - < 1 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 Repr. 2 ; H361d STOT RE 2 ; H373 Skin Irrit. 2 ; H315 STOT SE 3 ; H336

Additional information

The used hydrocarbons contain no benzene or benzene in concentrations less than 0.1 percent by weight and fulfil therefore the default(handicap) of the remark P to the appendix VI of the order (EC) No. 1272/2008 (GHS order).
For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Possible symptoms:

At eye contact: Irritation, burning, pain.

At skin contact: Irritation.

Irritation of the respiratory tract.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

At swallowing and vomiting danger of penetrating into the lungs.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO₂, powders or water spray for extinction. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Avoid contact with eyes and skin.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Ensure adequate ventilation. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8, information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use.

Measures to prevent fire

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-value. Keep away from ignition sources - No smoking. Ground/bond container and receiving equipment. Use explosion-proof pipes, electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep only in the original container. Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

Storage class (TRGS 510) : 3

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): M-VM 04.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 100 ppm / 440 mg/m³

Peak limitation : 4

Remark : Xylol

Version : 01.10.1993

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 20 ppm / 88 mg/m³

Peak limitation : 2(II)

Remark : Ethylbenzol H, Y, DFG

Version : 01.10.1993

Limit value type (country of origin) : STEL (EC)

Limit value : 200 ppm / 884 mg/m³

Remark : Ethylbenzol H

Version :

Limit value type (country of origin) : TWA (EC)

Limit value : 100 ppm / 442 mg/m³

Remark : Ethylbenzol H

Version :

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 62 ppm / 300 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 723 mg/m³
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 241 mg/m³
Version : 20.06.2019

BUTAN-1-OL ; CAS No. : 71-36-3

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 310 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 23.06.2022

HYDROCARBONS, C9, AROMATICS

Limit value type (country of origin) : TRGS 900 (D)
Parameter : Group limit for the calculation of the occupational exposure limit for hydrocarbon mixtures (see section 2.9 of Technical Rule 900).
Limit value : 50 mg/m³
Version :

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 500 ppm / 1200 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 23.06.2022

Limit value type (country of origin) : TWA (EC)
Limit value : 500 ppm / 1210 mg/m³
Version : 20.06.2019

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 200 ppm / 730 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 23.06.2022

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 190 mg/m³
Peak limitation : 2(II)
Remark : H, Y
Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 384 mg/m³
Remark : Skin
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 192 mg/m³
Remark : Skin
Version : 20.06.2019

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Remark

Short time value (STEL): Excess factor 2 (II) according to the german TRGS 900.
Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

Biological limit values

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Xylene / Whole blood (B) / End of exposure or end of shift

Limit value : 0,15 mg/dl

Remark : Xylol

Version : 01.10.1993

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift

Limit value : 2 g/l

Remark : Xylol

Version : 01.10.1993

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift

Limit value : 250 mg/g Creatinine

Remark : Ethylbenzol

Version : 01.10.1993

BUTAN-1-OL ; CAS No. : 71-36-3

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Butan-1-ol (1-butanol) (after hydrolysis) / Urine (U) / Before next shift

Limit value : 2 mg/g Creatinine

Version : 25.02.2022

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Butan-1-ol (1-butanol) (after hydrolysis) / Urine (U) / End of exposure or end of shift

Limit value : 10 mg/g Creatinine

Version : 25.02.2022

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Acetone / Urine (U) / End of exposure or end of shift

Limit value : 50 mg/l

Version : 25.02.2022

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Toluene / Whole blood (B) / after end of exposure (h): 0

Limit value : 600 µg/l

Version : 25.02.2022

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Toluene / Urine (U) / End of exposure or end of shift

Limit value : 75 µg/l

Version : 25.02.2022

Limit value type (country of origin) : TRGS 903 (D)

Parameter : O-cresol (after hydrolysis) / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts

Limit value : 1,5 mg/l

Version : 25.02.2022

DNEL-/PNEC-values

DNEL/DMEL

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type : DNEL Consumer (local)

Exposure route : Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Exposure frequency : Long-term
Limit value : = 65,3 mg/m³
Limit value type : DNEL Consumer (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 260 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : = 1,6 mg/kg
Assessment factor : 1 D
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 14,8 mg/m³
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 260 mg/m³
Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 289 mg/m³
Limit value type : DNEL worker (local and systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 221 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : = 211 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : = 442 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : = 180 mg/kg
Assessment factor : 1 D
N-BUTYL ACETATE ; CAS No. : 123-86-4
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 102,34 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 96 mg/kg
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 48 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Exposure frequency : Long-term
Limit value : 7 mg/kg
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 480 mg/m³

HYDROCARBONS, C9, AROMATICS

Limit value type : DNEL/DMEL (Consumer)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 11 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 32 mg/m³
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 11 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Professional)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 25 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Professional)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 150 mg/m³

ACETONE ; CAS No. : 67-64-1

Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 62 mg/kg
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 62 mg/kg
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 200 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 186 mg/kg
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 2420 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1210 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 734 mg/m³

Limit value type : DNEL worker (local)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 1468 mg/m³

Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 734 mg/m³

Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 1468 mg/m³

Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 63 mg/kg
Assessment factor : 1 D

PNEC

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,327 mg/l

Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : = 0,327 mg/l

Limit value type : PNEC (Sediment, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 12,64 mg/kg

Limit value type : PNEC (Sediment, marine water)
Exposure route : Water (Including sewage plant)
Limit value : = 12,64 mg/kg

Limit value type : PNEC soil
Exposure route : Soil
Limit value : 2,31 mg/kg

Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 6,58 mg/l

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,18 mg/l

Limit value type : PNEC (Aquatic, intermittent release)
Exposure route : Water (Including sewage plant)
Limit value : 0,36 mg/l

Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 0,018 mg/l

Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 0,981 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Limit value type : PNEC (Sediment, marine water)
Exposure route : Soil
Limit value : 0,0981 mg/kg

Limit value type : PNEC soil
Exposure route : Soil
Limit value : 0,0903 mg/kg

Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 35,6 mg/l

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 10,6 mg/l

Limit value type : PNEC (Aquatic, intermittent release)
Exposure route : Water (Including sewage plant)
Limit value : 21 mg/l

Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 1,06 mg/l

Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 30,4 mg/kg

Limit value type : PNEC (Sediment, marine water)
Exposure route : Soil
Limit value : 3,04 mg/kg

Limit value type : PNEC soil
Exposure route : Soil
Limit value : 0,112 mg/kg

Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 29,5 mg/l

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,24 mg/l

Limit value type : PNEC Intermittierende Einleitung
Exposure route : Water (Including sewage plant)
Limit value : 1,65 mg/l

Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 0,024 mg/l

Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 1,15 mg/kg

Limit value type : PNEC soil
Exposure route : Soil
Limit value : 0,148 mg/kg

Limit value type : PNEC Soil, Marine water
Exposure route : Soil
Limit value : 0,115 mg/kg

Limit value type : PNEC (Sewage treatment plant)
Exposure route : Water (Including sewage plant)
Limit value : 650 mg/l

8.2 Exposure controls

Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use safety glasses.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 60 min.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

Breathing protection equipment is not required in adequately ventilated places. Use suitable respiratory protective device in case of insufficient ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use the combination filter mask A2 - P3. Do not inhale the vapour.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : conformable to product designation.

Odour

Like solvent.

Safety characteristics

| | | |
|--------------------------------------------------|--------------|---------------------------------|
| Melting point/freezing point : | (1013 hPa) | No data available |
| Initial boiling point and boiling range : | (1013 hPa) | 100 - 150 °C |
| Decomposition temperature : | (1013 hPa) | No data available |
| Flash point : | | 21 °C |
| Auto-ignition temperature : | > | 200 °C |
| Lower explosion limit : | | No data available |
| Upper explosion limit : | | No data available |
| Vapour pressure : | (50 °C) | No data available |
| Density : | (20 °C) | approx. 0,875 g/cm ³ |
| Solvent separation test : | (20 °C) | < 3 % |
| Water solubility : | (20 °C) | practically insoluble |
| pH : | | not applicable |
| log P O/W : | | No data available |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024
Version (Revision) : 27.0.1 (27.0.0)

Flow time : (20 °C) < 90 s DIN-cup 4 mm
Kinematic viscosity : (40 °C) < 20,5 mm²/s
Relative vapour density : (20 °C) No data available
VOC-value : max. 880 g/l
Flammable liquids : The product is ignitable.
Particle Characteristics : not applicable

9.2 Other information

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

Cleaning cloths saturated with solvent can ignite themselves. Therefore ensure safe disposal of waste.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter : ATEmix calculated
Exposure route : Oral
Effective dose : 4000 mg/kg
Parameter : LD50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Exposure route : Oral
Species : Rat
Effective dose : 3523 - 4000 mg/kg
Parameter : LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Oral
Species : Rat
Effective dose : 10760 mg/kg
Parameter : LD50 (BUTAN-1-OL ; CAS No. : 71-36-3)
Exposure route : Oral
Species : Rat

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Effective dose : 790 mg/kg
Parameter : LD50 (HYDROCARBONS, C9, AROMATICS)
Exposure route : Oral
Species : Rat
Effective dose : > 6800 mg/kg
Parameter : LD50 (ACETONE ; CAS No. : 67-64-1)
Exposure route : Oral
Species : Rat
Effective dose : 9750 mg/kg
Parameter : LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Oral
Species : Rabbit
Effective dose : 4935 mg/kg
Parameter : LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Oral
Species : Rat
Effective dose : 11,3 g/kg
Parameter : LD50 (TOLUENE ; CAS No. : 108-88-3)
Exposure route : Oral
Species : Rat
Effective dose : 5000 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated
Exposure route : Dermal
Effective dose : 2477 mg/kg
Parameter : LD50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Exposure route : Dermal
Species : Rabbit
Effective dose : 12126 mg/kg
Parameter : LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 14000 mg/kg
Parameter : LD50 (BUTAN-1-OL ; CAS No. : 71-36-3)
Exposure route : Dermal
Species : Rabbit
Effective dose : 4200 mg/kg
Parameter : LD50 (HYDROCARBONS, C9, AROMATICS)
Exposure route : Dermal
Species : Rabbit
Effective dose : > 3400 mg/kg
Parameter : LD50 (ACETONE ; CAS No. : 67-64-1)
Exposure route : Dermal
Species : Rabbit
Effective dose : 20 g/kg
Parameter : LD50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Dermal
Species : Rat
Effective dose : 5000 mg/kg
Parameter : LD50 (TOLUENE ; CAS No. : 108-88-3)
Exposure route : Dermal
Species : Rabbit
Effective dose : 14 g/kg

Acute inhalation toxicity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Parameter : ATEmix calculated
Exposure route : Inhalation (vapour)
Effective dose : 24,8 mg/l

Parameter : LC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Exposure route : Inhalation (vapour)
Species : Rat
Effective dose : 10 - 20 mg/l
Exposure time : 4 h

Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Species : Rat
Effective dose : 23,4 mg/kg
Exposure time : 4 h

Parameter : LC50 (BUTAN-1-OL ; CAS No. : 71-36-3)
Exposure route : Inhalation
Species : Rat
Effective dose : 8000 ppm

Parameter : LC50 (HYDROCARBONS, C9, AROMATICS)
Exposure route : Inhalation
Species : Rat
Effective dose : > 10,2 mg/l
Exposure time : 4 h

Parameter : LC50 (ETHYL ACETATE ; CAS No. : 141-78-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 1600 mg/l

Parameter : LC50 (TOLUENE ; CAS No. : 108-88-3)
Exposure route : Inhalation
Species : Mouse
Effective dose : 5300 ppm

Corrosion

Irritation:

- On the eye: Causes serious eye damage.
- Respiratory: May cause irritation to the respiratory tract.
- On the skin: May cause irritation to the skin.

Respiratory or skin sensitisation

Sensitization: The product does not cause any skin and respiratory tract sensitization.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.

Symptoms and signs include headache: dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

The liquid splashed in the eyes may cause irritation and reversible damage.

STOT-repeated exposure

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Causes damage to the organs through prolonged or repeated exposure.

Aspiration hazard

Low quantities of the product can cause damage to the lungs, if the product enters into the lungs by swallowing or subsequent vomiting.

The product is classified as follows: May be fatal if swallowed and enters airways.

Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

| | |
|------------------------|---------------------------------------------------|
| Parameter : | LC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE) |
| Species : | Acute (short-term) fish toxicity |
| Evaluation parameter : | Oncorhynchus mykiss |
| Effective dose : | = 2,6 mg/l |
| Exposure time : | 96 h |
| Parameter : | LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Species : | Pimephales promelas (fathead minnow) |
| Effective dose : | 18 mg/l |
| Exposure time : | 96 h |
| Parameter : | LC50 (HYDROCARBONS, C9, AROMATICS) |
| Species : | Oncorhynchus mykiss (Rainbow trout) |
| Effective dose : | 9,2 mg/l |
| Exposure time : | 96 h |

Acute (short-term) toxicity to crustacea

| | |
|------------------------|---------------------------------------------------|
| Parameter : | LC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE) |
| Species : | Acute (short-term) toxicity to crustacea |
| Evaluation parameter : | Daphnia magna |
| Effective dose : | = 1 mg/l |
| Exposure time : | 24 h |
| Parameter : | EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Species : | Daphnia magna (Big water flea) |
| Effective dose : | 44 mg/l |
| Exposure time : | 48 h |
| Parameter : | EC50 (HYDROCARBONS, C9, AROMATICS) |
| Species : | Daphnia magna (Big water flea) |
| Effective dose : | 3,2 mg/l |
| Exposure time : | 48 h |

Acute (short-term) toxicity to algae and cyanobacteria

| | |
|------------------------|--------------------------------------------------------|
| Parameter : | EC50 (REACTION MASS OF ETHYLBENZENE AND XYLENE) |
| Species : | Scenedesmus capricornutum |
| Evaluation parameter : | Acute (short-term) toxicity to algae and cyanobacteria |
| Effective dose : | = 2,2 mg/l |
| Exposure time : | 73 h |
| Parameter : | EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Species : | Desmodesmus subspicatus |
| Effective dose : | 647,7 mg/l |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Exposure time : 72 h
Parameter : EL50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Desmodemus subspicatus
Effective dose : 200 mg/l
Parameter : EC50 (BUTAN-1-OL ; CAS No. : 71-36-3)
Species : Daphnia magna (Big water flea)
Effective dose : 1855 mg/l
Parameter : ErC50 (HYDROCARBONS, C9, AROMATICS)
Species : Pseudokirchneriella subcapitata
Effective dose : 2,6 - 2,9 mg/l
Exposure time : 72 h

Sewage treatment plant

Parameter : Effects in sewage plants (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Inoculum : Activated sludge
Effective dose : = 16 mg/l
Exposure time : 28 D

12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

Biodegradation

Parameter : Biodegradation (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : = 90 %
Test duration : 28 D

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (REACTION MASS OF ETHYLBENZENE AND XYLENE)
Bioconcentration factor (BCF)
Value : = 25,9

These are not data available about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas available about the potential of the product concerning his mobility in the ground.
A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Harmful to aquatic life, may cause long-term adverse effects in the aquatic environment.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations.
Packaging with not dry uped residues have to dropped at official collecting sites. Do not empty into waters or drains.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

Waste codes/waste designations according to EWC/AVV

For the product:
Disposal-definition No. in accordance with the ordinance over the European waste list (waste list ordinance): 07 03 04 * other organic solvents, washing liquids and mother liquors.

After intended use

Only empty packaging can be transferred to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:
Code of the European waste catalogue (EWC-Code):
15 01 10* - packaging containing residues of or contaminated by hazardous substances.

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT RELATED MATERIAL

Sea transport (IMDG)

PAINT RELATED MATERIAL

Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 33
Tunnel restriction code : D/E
Special provisions : 640D · LQ 5 I · E 2 · ADR : III (<= 450 l)
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 5 I · E 2 · Packing group
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 2 · IATA 3.3.3.1 (Packing group III <= 30 l)
Hazard label(s) : 3

14.4 Packing group

II

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions):

Use restriction according to REACH annex XVII, no. : 3, 40, 48, 75

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

Labelling for contents according to regulation (EC) No. 648/2004

≥ 30 % aromatic hydrocarbons.

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : 0,5 - 0,99 %

Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

Additional information

The product is not classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils not the criteria for solid substances according to the TRwS 779 number 2.1.1.

Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 15. Restrictions on use · 15. Water hazard class

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds
ATEmix: Calculated acute toxicity estimate of mixture
BCF: Bio-Concentration Factor
CAS: Chemical Abstract Service
CLP: Classification, Labelling and Packaging
CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction
CSR: Chemical Safety Report
DNEL: Derived No Effect Level
EC: European Commission
EC50: Effective Concentration 50%
ECHA: European Chemical Agency
EEC: European Economic Community
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EWC: European Waste Catalogue

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456

Revision date : 25.01.2024

Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IC50: Inhibition Concentration 50%
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Lethal concentration 50%
LD50: Lethal Dose 50%
LOAEL: Lowest Observed Adverse Effect Level
LOEL: Lowest observable effect level
MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)
MARPOL: Convention for the Prevention of Marine Pollution from Ships
MVZ: molar ratio
n.a.: Not applicable
n.d.: Not determined
n.r.: Not relevant
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OEL: Occupational Exposure Limit
PBT: Persistent, bioaccumulative, toxic
PNEC: Predicted No Effect Concentration
RCP: Reciprocal calculation procedure
REACH: Registration, Evaluation and Authorization of Chemical
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
SVHC: Substance of Very High Concern
TLV - TWA: Threshold Limit Value - Time Weighed Average
VOC: Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

| | |
|--------|--------------------------------------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

16.6 Training advice

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Nitro Thinner 456
Nitro-Verdünnung 456
Revision date : 25.01.2024
Print date : 25.01.2024

Version (Revision) : 27.0.1 (27.0.0)

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
