

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

##### Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

#### Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Brillux GmbH & Co KG  
www.brillux.de

**Street :** Weseler Straße 401

**Postal code/City :** D - 48163 Münster

**Telephone :** +49 (0)251-7188-0

**Telefax :** +49 (0)251-7188-280

#### Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

### 1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):  
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)  
Telephone: +49 (0)551-19240.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

### Signal word

Danger

### Hazard components for labelling

ETHYL ACETATE ; CAS No. : 141-78-6

XYLENE ; CAS No. : 1330-20-7

ETHYLBENZENE ; CAS No. : 100-41-4

### Hazard statements

- H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

- P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or a doctor.  
P331 Do NOT induce vomiting.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P501 Dispose of contents/container to approved disposal company or local collection.

### 2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Description

Solvent mixture based on aromatic hydrocarbons, esters and alcohols.

#### Hazardous ingredients

ETHYL ACETATE ; REACH No. : 01-2119475103-46 ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction :  $\geq 45 - < 50$  %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 EUH066

XYLENE ; REACH No. : 01-2119488216-32 ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 40 - < 45$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

ETHYLBENZENE ; REACH No. : 01-2119489370-35 ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction :  $\geq 10 - < 15$  %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H332

PROPAN-2-OL ; REACH No. : 01-2119457558-25 ; EC No. : 200-661-7; CAS No. : 67-63-0

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

#### Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

#### In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

#### After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

#### Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation, eye irritation and irritation to respiratory tract are possible. At swallowing and vomiting danger of penetrating into the lungs.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO<sub>2</sub>, powders or water spray for extinction. Fight larger fires with water spray or alcohol resistant foam.

#### Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting.

### 5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Avoid contact with eyes and skin.

### 6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Ensure adequate ventilation. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
You find information about the safety equipment of persons in the section 8,  
information about the refuse disposal in section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use.

#### Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-value. Keep away from ignition sources - No smoking. Ground/bond container and receiving equipment. Use explosion-proof pipes, electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

#### Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep only in the original container. Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

**Storage class (TRGS 510) :** 3

#### Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

### 7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

## Industrial sector specific solutions

**GISCODE :** Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): M-VM 04.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 730 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 02.07.2021

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 440 mg/m<sup>3</sup>  
Peak limitation : 4  
Version : 01.10.1993

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H, Y, DFG  
Version : 02.07.2009

Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : H  
Version : 08.06.2000

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 500 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : Y  
Version : 02.07.2021

#### Remark

Short time value (STEL): Excess factor 2 (II) according to the german TRGS 900.  
Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

#### Biological limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift  
Limit value : 2000 mg/l  
Version : 01.10.1993

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift  
Limit value : 250 mg/g Creatinine

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

---

Version : 31.03.2004  
PROPAN-2-OL ; CAS No. : 67-63-0  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Acetone / Whole blood (B) / End of exposure or end of shift  
Limit value : 25 mg/l  
Version : 04.05.2021  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Acetone / Urine (U) / End of exposure or end of shift  
Limit value : 25 mg/l  
Version : 04.05.2021

## DNEL-/PNEC-values

### DNEL/DMEL

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 734 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 1468 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 734 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 1468 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 63 mg/kg  
Assessment factor : 1 D

XYLENE ; CAS No. : 1330-20-7

Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 174 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 14,8 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 1,6 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 108 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Professional)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 289 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Professional)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 174 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Professional)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 77 mg/m<sup>3</sup>

**ETHYLBENZENE ; CAS No. : 100-41-4**

Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 289 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 77 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 180 mg/kg

**PROPAN-2-OL ; CAS No. : 67-63-0**

Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 26 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 319 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 89 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 888 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 500 mg/m<sup>3</sup>

**PNEC**

**ETHYL ACETATE ; CAS No. : 141-78-6**

Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,24 mg/l  
Limit value type : PNEC Intermittierende Einleitung  
Exposure route : Water (Including sewage plant)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

---

Limit value : 1,65 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,024 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Soil  
Limit value : 1,15 mg/kg  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 0,148 mg/kg  
Limit value type : PNEC Soil, Marine water  
Exposure route : Soil  
Limit value : 0,115 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 650 mg/l

XYLENE ; CAS No. : 1330-20-7  
Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,327 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 12,46 mg/kg  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 2,31 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 6,58 mg/l

PROPAN-2-OL ; CAS No. : 67-63-0  
Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 140,9 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : 140,9 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Soil  
Limit value : 552 mg/kg  
Assessment factor : 1 D  
Limit value type : PNEC (Sediment, marine water)  
Exposure route : Soil  
Limit value : 552 mg/kg  
Assessment factor : 1 D  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 28 mg/kg  
Assessment factor : 1 D  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 2251 mg/l

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

## Personal protection equipment

### Eye/face protection

Use safety glasses.

### Skin protection

#### Hand protection

At use as agreed a protective gloves from nitrile rubber with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 60 min.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

#### Body protection

Using protective clothing.

### Respiratory protection

Breathing protection equipment is not required in adequately ventilated places. Use suitable respiratory protective device in case of insufficient ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use the combination filter mask A2 - P3. Do not inhale the vapour.

## General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

## Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state :** Liquid.

**Colour :** conformable to product designation.

#### Odour

Like organic solvent.

#### Safety characteristics

<b>Melting point/freezing point :</b>	( 1013 hPa )		No data available		
<b>Initial boiling point and boiling range :</b>	( 1013 hPa )	approx.	120 - 200	°C	
<b>Decomposition temperature :</b>	( 1013 hPa )		No data available		
<b>Flash point :</b>		<	21	°C	
<b>Auto-ignition temperature :</b>		>	400	°C	
<b>Lower explosion limit :</b>			1	Vol-%	
<b>Upper explosion limit :</b>			7	Vol-%	
<b>Vapour pressure :</b>	( 50 °C )		No data available		
<b>Density :</b>	( 20 °C )	approx.	0,87 - 0,89	g/cm <sup>3</sup>	
<b>Solvent separation test :</b>	( 20 °C )	<	3	%	
<b>Water solubility :</b>	( 20 °C )		practically insoluble		
<b>pH :</b>			not applicable		
<b>log P O/W :</b>			No data available		
<b>Flow time :</b>	( 20 °C )	<	90	s	DIN-cup 4 mm
<b>Kinematic viscosity :</b>	( 40 °C )	<	20,5	mm <sup>2</sup> /s	

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

**Relative vapour density :** ( 20 °C ) No data available

**VOC-value :** max. 890 g/l

**Flammable liquids :** The product is ignitable.

**Particle Characteristics :** not applicable

## 9.2 Other information

Other physical and chemical data have not been determined.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

### 10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

Cleaning cloths saturated with solvent can ignite themselves. Therefore ensure safe disposal of waste.

### 10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

#### Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Exposure route :	Oral
Species :	Rabbit
Effective dose :	4935 mg/kg
Parameter :	LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	11,3 g/kg
Parameter :	LD50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	4300 mg/kg
Parameter :	LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

Exposure route : Oral  
Species : Rat  
Effective dose : 3500 mg/kg  
Parameter : LD50 ( PROPAN-2-OL ; CAS No. : 67-63-0 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 5840 mg/kg

### Acute dermal toxicity

Parameter : ATEmix calculated  
Exposure route : Dermal  
Effective dose : 2750 mg/kg  
Parameter : LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : 5000 mg/kg  
Parameter : LD50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 2000 mg/kg  
Parameter : LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 5000 mg/kg

### Acute inhalation toxicity

Parameter : ATEmix calculated  
Exposure route : Inhalation (vapour)  
Effective dose : 22 mg/l  
Parameter : LC50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 1600 mg/l  
Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 22 mg/l  
Exposure time : 4 h  
Parameter : LC50 ( PROPAN-2-OL ; CAS No. : 67-63-0 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 47,5 mg/l  
Exposure time : 8 h

### Corrosion

Irritation:  
- Skin contact: Irritating to skin.  
- Eye contact: Causes serious eye irritation.  
- Respiratory tract: Irritation of the respiratory tract possible.

### Respiratory or skin sensitisation

Sensitization: The product does not cause any skin and respiratory tract sensitization.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

### STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

Symptoms and signs include headache: dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

The liquid splashed in the eyes may cause irritation and reversible damage.

### STOT-repeated exposure

May cause damage to the organs through prolonged or repeated exposure.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

### Aspiration hazard

Low quantities of the product can cause damage to the lungs, if the product enters into the lungs by swallowing or subsequent vomiting.

The product is classified as follows: May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

### Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

### Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Effective dose : 2,6 mg/l  
Exposure time : 96 h

##### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 1 - 10 mg/l  
Exposure time : 48 h

##### Acute (short-term) toxicity to algae and cyanobacteria

Parameter : IC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Scenedesmus subspicatus  
Effective dose : 2,2 mg/l

##### Toxicity to microorganisms

Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Bacteria toxicity  
Effective dose : 96 mg/l  
Exposure time : 24 h

### 12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

#### Biodegradation

Parameter : Biodegradation ( XYLENE ; CAS No. : 1330-20-7 )  
Inoculum : Biodegradation  
Degradation rate : > 60 %

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

Test duration : 28 D

## 12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.

## 12.4 Mobility in soil

These are not data available about the potential of the product concerning his mobility in the ground.  
A penetrating into soil, waters and sewage system should be prevented.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

## 12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

## 12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations.  
Packaging with not dry uped residues have to dropped at official collecting sites. Do not empty into waters or drains.

##### Waste codes/waste designations according to EWC/AVV

Disposal-definition No. in accordance with the ordinance over the European waste list (waste list ordinance - AVV):  
07 03 04 \* other organic solvents, washing liquids and nut lyes.

##### After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

##### Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Disposal-definition No.:

15 01 10 \* packings which contain dangerous substances or are polluted by dangerous substances.

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

PAINT RELATED MATERIAL

#### Sea transport (IMDG)

PAINT RELATED MATERIAL

#### Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3

**Classification code :** F1

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

**Hazard identification number (Kemler No.) :** 33

**Tunnel restriction code :** D/E

**Special provisions :** 640D · LQ 5 I · E 2

**Hazard label(s) :** 3

#### Sea transport (IMDG)

**Class(es) :** 3

**EmS-No. :** F-E / ~~S-E~~

**Special provisions :** LQ 5 I · E 2

**Hazard label(s) :** 3

#### Air transport (ICAO-TI / IATA-DGR)

**Class(es) :** 3

**Special provisions :** E 2

**Hazard label(s) :** 3

#### 14.4 Packing group

II

#### 14.5 Environmental hazards

**Land transport (ADR/RID) :** No

**Sea transport (IMDG) :** No

**Air transport (ICAO-TI / IATA-DGR) :** No

#### 14.6 Special precautions for user

None

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

##### Other regulations (EU)

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the emissions of volatile organic compounds due to the use of organic solvents in certain colours and varnishes.

##### Labelling for contents according to regulation (EC) No. 648/2004

≥ 30 % aromatic hydrocarbons.

##### National regulations

##### Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

##### Additional information

The product is not classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils not the criteria for solid substances according to the TRWS 779 number 2.1.1.

Maternity regulations and Young Persons Employment Act are to take into account.

#### 15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

### SECTION 16: Other information

#### 16.1 Indication of changes

None

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

**Print date :** 15.02.2022

### 16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)  
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds  
ATEmix: Calculated acute toxicity estimate of mixture  
BCF: Bio-Concentration Factor  
CAS: Chemical Abstract Service  
CLP: Classification, Labelling and Packaging  
CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction  
CSR: Chemical Safety Report  
DNEL: Derived No Effect Level  
EC: European Commission  
EC50: Effective Concentration 50%  
ECHA: European Chemical Agency  
EEC: European Economic Community  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
EWC: European Waste Catalogue  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
IC50: Inhibition Concentration 50%  
IMDG Code: International Maritime Dangerous Goods Code  
IMO: International Maritime Organization  
LC50: Lethal concentration 50%  
LD50: Lethal Dose 50%  
LOAEL: Lowest Observed Adverse Effect Level  
LOEL: Lowest observable effect level  
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)  
MARPOL: Convention for the Prevention of Marine Pollution from Ships  
MVZ: molar ratio  
n.a.: Not applicable  
n.d.: Not determined  
n.r.: Not relevant  
NLP: No Longer Polymers  
NOAEC: No Observed Adverse Effect Concentration  
NOAEL: No Observed Adverse Effect Level  
NOEC: No Observed Effect Concentration  
NOEL: No Observed Effect Level  
OEL: Occupational Exposure Limit  
PBT: Persistent, bioaccumulative, toxic  
PNEC: Predicted No Effect Concentration  
RCP: Reciprocal calculation procedure  
REACH: Registration, Evaluation and Authorization of Chemical  
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)  
STEL: Short-term Exposure Limit  
SVHC: Substance of Very High Concern  
TLV - TWA: Threshold Limit Value - Time Weighted Average  
VOC: Volatile Organic Compounds  
vPvB: Very persistent, very bioaccumulative.

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Cleaner and Degreasing Agent 614  
Reiniger und Entfetter 614

**Revision date :** 15.02.2022

**Print date :** 15.02.2022

**Version (Revision) :** 14.0.0 (13.0.1)

---

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

### 16.6 Training advice

None

### 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---