

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Spray Paint Exhaust 671
Sprühlack Auspuff 671

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG
www.brillux.de

Street : Weseler Straße 401

Postal code/City : D - 48163 Münster

Telephone : +49 (0)251-7188-0

Telefax : +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)
Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1 ; H222 - Aerosols : Category 1 ; Extremely flammable aerosol.

Aerosol 1 ; H229 - Aerosols : Category 1 ; Pressurised container: May burst if heated.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

ACETONE ; CAS No. : 67-64-1

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671

Revision date : 13.11.2024

Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

N-BUTYL ACETATE ; CAS No. : 123-86-4
2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P501 Dispose of contents/container to approved disposal company or local collection.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P337+P313 If eye irritation persists: Get medical advice/attention.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

Adverse physicochemical effects

Caution! Pressurized container.
Without sufficient ventilation formation of explosive mixtures may be possible.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Mixture based on components, which are called following, and other components.

Hazardous ingredients

PROPANE ; REACH No. : 01-2119486944-21 ; EC No. : 200-827-9; CAS No. : 74-98-6

Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280

BUTANE ; REACH No. : 01-2119474691-32 ; EC No. : 203-448-7; CAS No. : 106-97-8

Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280

DIMETHYL ETHER ; REACH No. : 01-2119472128-37 ; EC No. : 204-065-8; CAS No. : 115-10-6

Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280

ACETONE ; REACH No. : 01-2119471330-49 ; EC No. : 200-662-2; CAS No. : 67-64-1

Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336 O223 EUH066

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction : $\geq 10 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

ISOBUTANE ; REACH No. : 01-2119485395-27 ; EC No. : 200-857-2; CAS No. : 75-28-5

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280

2-METHOXY-1-METHYLETHYL ACETATE ; REACH No. : 01-2119475791-29 ; EC No. : 203-603-9; CAS No. : 108-65-6

Weight fraction : $\geq 2,5 - < 5 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

PROPYLENE CARBONATE ; EC No. : 203-572-1; CAS No. : 108-32-7

Weight fraction : $< 1 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

2-METHYLPROPAN-1-OL ; REACH No. : 01-2119484609-23 ; EC No. : 201-148-0; CAS No. : 78-83-1

Weight fraction : $< 1 \%$

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 STOT SE 3 ; H336

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation, eye irritation and irritation to respiratory tract are possible.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO₂, powders or water spray for extinction. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

5.2 Special hazards arising from the substance or mixture

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Hazardous combustion products

Can form explosive gas-air mixtures. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep no protective persons away, personal should wear protective clothings. Refer to protective measures listed in sections 7 and 8. Avoid contact with eyes and skin. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Ensure adequate ventilation. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8, information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Keep away from heat and direct sunlight. Ensure a good ventilation in room and working area. Avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit) or other thresholds. Vapours are heavier than air - ensure a good ventilation in room and working area. Read label before use.

Measures to prevent fire

Keep ignition sources away - Do not smoke. Container is under pressure. Protect against sunshine and heating over 50 °C. After use: do not open violently or burn. Do not spray into flames or on glowing materials.

Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Observe official regulations on storing packagings with pressurized containers. Store in a well-ventilated place. Keep cool. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Do not store the product in lounge room. Keep out of the reach of children.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

Storage class (TRGS 510) : 2B

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : This product can not be encoded in accordance with GISBAU.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

PROPANE ; CAS No. : 74-98-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1000 ppm / 1800 mg/m³
Peak limitation : 4(II)
Version : 12.06.2023

BUTANE ; CAS No. : 106-97-8

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1000 ppm / 2400 mg/m³
Peak limitation : 4(II)
Version : 12.06.2023

DIMETHYL ETHER ; CAS No. : 115-10-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1000 ppm / 1900 mg/m³
Peak limitation : 8(II)
Version : 12.06.2023

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 500 ppm / 1200 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 12.06.2023

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 62 ppm / 300 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 12.06.2023

ISOBUTANE ; CAS No. : 75-28-5

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1000 ppm / 2400 mg/m³
Peak limitation : 4(II)
Version : 12.06.2023

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 270 mg/m³
Peak limitation : 1(I)
Remark : Y

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Version : 12.06.2023
PROPYLENE CARBONATE ; CAS No. : 108-32-7
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 2 ppm / 8,5 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 12.06.2023
2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 310 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 12.06.2023

Remark

Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

Biological limit values

ACETONE ; CAS No. : 67-64-1
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Urine (U) / End of exposure or end of shift
Limit value : 50 mg/l
Version : 12.06.2023

DNEL-/PNEC-values

DNEL/DMEL

ACETONE ; CAS No. : 67-64-1
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 62 mg/kg
DIMETHYL ETHER ; CAS No. : 115-10-6
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 497 mg/m³
ACETONE ; CAS No. : 67-64-1
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 62 mg/kg
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 200 mg/m³
N-BUTYL ACETATE ; CAS No. : 123-86-4
Limit value type : DNEL Consumer (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 102,34 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 96 mg/kg
ACETONE ; CAS No. : 67-64-1
Limit value type : DNEL/DMEL (Industrial)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671

Revision date : 13.11.2024

Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 186 mg/kg
Limit value type : DNEL/DMEL (Industrial)

Exposure route : Inhalation
Exposure frequency : Short-term
Limit value : 2420 mg/m³

N-BUTYL ACETATE ; CAS No. : 123-86-4
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 48 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 7 mg/kg

ACETONE ; CAS No. : 67-64-1
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1210 mg/m³

N-BUTYL ACETATE ; CAS No. : 123-86-4
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 480 mg/m³

DIMETHYL ETHER ; CAS No. : 115-10-6
Limit value type : DNEL/DMEL (Professional)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1894 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 54,8 mg/kg
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 33 mg/m³
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral
Exposure frequency : Long-term
Limit value : 1,67 mg/kg
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 275 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 153,5 mg/kg

2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Oral

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Exposure frequency : Long-term
Limit value : 25 mg/kg
Assessment factor : 1 D
Limit value type : DNEL/DMEL (Consumer)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 55 mg/m³
Limit value type : DNEL/DMEL (Industrial)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 310 mg/m³

PNEC

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,18 mg/l

DIMETHYL ETHER ; CAS No. : 115-10-6

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 0,155 mg/l

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)
Limit value : 10,6 mg/l
Limit value type : PNEC (Aquatic, intermittent release)
Exposure route : Water (Including sewage plant)
Limit value : 21 mg/l

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, intermittent release)
Exposure route : Water (Including sewage plant)
Limit value : 0,36 mg/l
Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 0,018 mg/l

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC (Aquatic, marine water)
Exposure route : Water (Including sewage plant)
Limit value : 1,06 mg/l

DIMETHYL ETHER ; CAS No. : 115-10-6

Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,016 mg/l
Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 0,681 mg/kg
Assessment factor : 1 D

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 30,4 mg/kg

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Sediment, freshwater)
Exposure route : Soil
Limit value : 0,981 mg/kg
Limit value type : PNEC (Sediment, marine water)
Exposure route : Soil

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671

Revision date : 13.11.2024

Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Limit value : 0,0981 mg/kg

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC (Sediment, marine water)

Exposure route : Soil

Limit value : 3,04 mg/kg

DIMETHYL ETHER ; CAS No. : 115-10-6

Limit value type : PNEC (Sediment, marine water)

Exposure route : Soil

Limit value : 0,069 mg/kg

Assessment factor : 1 D

Limit value type : PNEC soil

Exposure route : Soil

Limit value : 0,045 mg/kg

Assessment factor : 1 D

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC soil

Exposure route : Soil

Limit value : 0,112 mg/kg

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC soil

Exposure route : Soil

Limit value : 0,0903 mg/kg

DIMETHYL ETHER ; CAS No. : 115-10-6

Limit value type : PNEC (Soil)

Limit value : 0,45 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Exposure route : Water (Including sewage plant)

Limit value : 160 mg/l

ACETONE ; CAS No. : 67-64-1

Limit value type : PNEC (Sewage treatment plant)

Exposure route : Water (Including sewage plant)

Limit value : 29,5 mg/l

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Sewage treatment plant)

Exposure route : Water (Including sewage plant)

Limit value : 35,6 mg/l

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type : PNEC (Aquatic, freshwater)

Exposure route : Water (Including sewage plant)

Limit value : 0,635 mg/l

Limit value type : PNEC (Aquatic, marine water)

Exposure route : Water (Including sewage plant)

Limit value : 0,0635 mg/l

Limit value type : PNEC (Sediment, freshwater)

Exposure route : Soil

Limit value : 3,29 mg/kg

Limit value type : PNEC (Sediment, marine water)

Exposure route : Soil

Limit value : 0,329 mg/kg

Limit value type : PNEC soil

Exposure route : Soil

Limit value : 29 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Exposure route : Water (Including sewage plant)

Limit value : 100 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671

Revision date : 13.11.2024

Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1

Limit value type :	PNEC (Aquatic, freshwater)
Exposure route :	Water (Including sewage plant)
Limit value :	0,4 mg/l
Limit value type :	PNEC (Aquatic, marine water)
Exposure route :	Water (Including sewage plant)
Limit value :	0,04 mg/l
Limit value type :	PNEC (Sediment, freshwater)
Exposure route :	Soil
Limit value :	1,52 mg/kg
Limit value type :	PNEC (Sediment, marine water)
Exposure route :	Soil
Limit value :	0,125 mg/kg
Limit value type :	PNEC soil
Exposure route :	Soil
Limit value :	0,0699 mg/kg
Limit value type :	PNEC (Sewage treatment plant)
Exposure route :	Water (Including sewage plant)
Limit value :	10 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use safety glasses.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 60 min.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

Use suitable respiratory protective device in case of insufficient ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use the combination filter mask A2 - P3. Do not breathe gas or spray.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe gas or spray.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Appearance

Aerosol.

Colour : conformable to product designation.

Odour

Smell of organic solvents.

Safety characteristics

Melting point/freezing point :	(1013 hPa)	No data available
Initial boiling point and boiling range :	(1013 hPa)	-44 °C
Decomposition temperature :	(1013 hPa)	No data available
Flash point :	<	0 °C
Auto-ignition temperature :		235 °C
Lower explosion limit :		1,2 Vol-%
Upper explosion limit :		18,6 Vol-%
Vapour pressure:	(20 °C)	3600 hPa
Density :	(20 °C)	0,748 g/cm ³
Water solubility :	(20 °C)	completely miscible
pH :		not applicable
log P O/W :		No data available
Viscosity :	(20 °C)	No data available
Kinematic viscosity :	(40 °C)	No data available
Solid content :		7 Weight-%
Solvent content :		93 Weight-%
Relative vapour density :	(20 °C)	No data available
VOC-value :	<	840 g/l
Aerosols :	Extremely flammable.	
Particle Characteristics :	not applicable	

9.2 Other information

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	10760 mg/kg
Parameter :	LD50 (ACETONE ; CAS No. : 67-64-1)
Exposure route :	Oral
Species :	Rat
Effective dose :	9750 mg/kg
Parameter :	LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Oral
Species :	Rat
Effective dose :	8500 mg/kg
Parameter :	LD50 (PROPYLENE CARBONATE ; CAS No. : 108-32-7)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route :	Oral
Species :	Rat
Effective dose :	2830 mg/kg

Acute dermal toxicity

Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 14000 mg/kg
Parameter :	LD50 (ACETONE ; CAS No. : 67-64-1)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	20 g/kg
Parameter :	LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 (PROPYLENE CARBONATE ; CAS No. : 108-32-7)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route :	Dermal
Species :	Rat
Effective dose :	3400 mg/kg
Exposure time :	4 h

Acute inhalation toxicity

Parameter :	LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	23,4 mg/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671

Revision date : 13.11.2024

Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Exposure time :	4 h
Parameter :	LC50 (BUTANE ; CAS No. : 106-97-8)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	659 g/m ³
Parameter :	LC50 (DIMETHYL ETHER ; CAS No. : 115-10-6)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	308 mg/l
Parameter :	LC50 (BUTANE ; CAS No. : 106-97-8)
Exposure route :	Inhalation
Species :	Mouse
Effective dose :	680 g/m ³
Parameter :	LC50 (ISOBUTANE ; CAS No. : 75-28-5)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	57 pph
Parameter :	LC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	35,7 mg/l
Parameter :	LC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	8000 ppm

Corrosion

Irritation:

- Skin contact: Repeated exposure may cause skin dryness or cracking.
- Eye contact: Causes serious eye irritation.

Respiratory or skin sensitisation

A sensitizing effect by the product is not known.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.

Symptoms and signs include headache: dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

The liquid splashed in the eyes may cause irritation and reversible damage.

STOT-repeated exposure

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Aspiration hazard

The product contains substances, which are classified as aspiration toxicity, category 1 (May be fatal if swallowed and enters airways), in accordance to the Regulation (EC) No. 1272/2008 (CLP-Regulation) in their pure form. Based on available data the classification criteria according to Regulation (EC) No 1272/2008 [CLP] are not fulfilled.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter :	LC50 (DIMETHYL ETHER ; CAS No. : 115-10-6)
Species :	Poecilia reticulata (Guppy)
Effective dose :	> 4,1 g/l
Exposure time :	96 h
Parameter :	LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species :	Pimephales promelas (fathead minnow)
Effective dose :	18 mg/l
Exposure time :	96 h
Parameter :	LC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species :	Oryzias latipes (Ricefish)
Effective dose :	> 100 mg/l
Exposure time :	96 h
Parameter :	LC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species :	Pimephales promelas (fathead minnow)
Effective dose :	1430 mg/l
Exposure time :	96 h
Parameter :	LC50 (PROPYLENE CARBONATE ; CAS No. : 108-32-7)
Species :	Leuciscus idus (golden orfe)
Effective dose :	5300 mg/l
Exposure time :	96 h

Chronic (long-term) fish toxicity

Parameter :	NOEC (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species :	Oryzias latipes (Ricefish)
Effective dose :	47,5 mg/l
Exposure time :	14 D

Acute (short-term) toxicity to crustacea

Parameter :	EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species :	Daphnia magna (Big water flea)
Effective dose :	44 mg/l
Exposure time :	48 h
Parameter :	LC50 (DIMETHYL ETHER ; CAS No. : 115-10-6)
Species :	Daphnia magna (Big water flea)
Effective dose :	> 4400 mg/l
Parameter :	EC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species :	Daphnia magna (Big water flea)
Effective dose :	> 500 mg/l
Exposure time :	48 h
Parameter :	EC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species :	Daphnia magna (Big water flea)
Effective dose :	1100 mg/l
Exposure time :	48 h
Parameter :	EC50 (PROPYLENE CARBONATE ; CAS No. : 108-32-7)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Effective dose : > 500 mg/l
Exposure time : 48 h

Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species : Daphnia magna (Big water flea)
Effective dose : > 100 mg/l
Exposure time : 21 D
Parameter : NOEC (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Daphnia magna (Big water flea)
Effective dose : 20 mg/l
Exposure time : 21 D

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Desmodesmus subspicatus
Effective dose : 647,7 mg/l
Exposure time : 72 h
Parameter : EL50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Desmodesmus subspicatus
Effective dose : 200 mg/l
Parameter : ErC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species : Pseudokirchneriella subcapitata
Effective dose : > 1000 mg/l
Exposure time : 3 h
Parameter : EC50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Pseudokirchneriella subcapitata
Effective dose : 632 mg/l
Exposure time : 72 h
Parameter : EC50 (PROPYLENE CARBONATE ; CAS No. : 108-32-7)
Effective dose : > 500 mg/l
Exposure time : 72 h
Parameter : EL50 (2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1)
Species : Pseudokirchneriella subcapitata
Effective dose : 53 mg/l
Exposure time : 72 h

Toxicity to microorganisms

Parameter : EC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Species : Mysidopsis bahia
Effective dose : > 1000 mg/l
Exposure time : 0,5 h
Parameter : EC50 (PROPYLENE CARBONATE ; CAS No. : 108-32-7)
Effective dose : > 10000 mg/l
Exposure time : 17 h

12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

Biodegradation

Parameter : Biodegradation (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Inoculum : Biodegradation
Degradation rate : 100 %
Test duration : 8 D
Parameter : Biodegradation (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Inoculum : Biodegradation
Degradation rate : > 90 %
Test duration : 28 D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not data available about the potential of the product concerning his mobility in the ground.
A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.
Avoid exposing into ground, waterways and drainage.
Danger of drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations.
Packaging with not dry uped residues have to dropped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

Waste codes/waste designations according to EWC/AVV

For the product:

Code of the European waste catalogue (EWC-Code):

08 01 11* Paint and varnish waste which contains organic solvents or other dangerous substances.

After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Code of the European waste catalogue (EWC-Code):

15 01 10* - packaging containing residues of or contaminated by hazardous substances.

SECTION 14: Transport information

14.1 UN number

UN 1950

14.2 UN proper shipping name

Land transport (ADR/RID)

AEROSOLS

Sea transport (IMDG)

AEROSOLS

Air transport (ICAO-TI / IATA-DGR)

AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

Class(es) : 2
Classification code : 5F
Hazard identification number (Kemler No.) : 23
Tunnel restriction code : D
Special Provisions : LQ 1 | · E 0
Hazard label(s) : 2.1

Sea transport (IMDG)

Class(es) : 2.1
EmS-No. : F-D / S-U
Special Provisions : LQ 1 | · E 0
Hazard label(s) : 2.1

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 2.1
Hazard label(s) : 2.1

14.4 Packing group

-

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

14.8 Additional information

ADR/RID: Limited quantities.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Product sub-category and VOC limiting values in accordance with appendix II, letter B of the guideline:

Category e;

VOC limiting value of the category from 01.01.2007: 840 g/l.

This product contains max. 700 g/l VOC.

Regulation (EU) 2019/1148 (marketing and use of explosives precursors)

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulations

Water hazard class

Self-classification - Class : 1 (Slightly hazardous to water)

Additional information

Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671

Revision date : 13.11.2024

Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor

CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report

DNEL: Derived No Effect Level

EC: European Commission

EC50: Effective Concentration 50%

ECHA: European Chemical Agency

EEC: European Economic Community

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EWG: European Waste Catalogue

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IC50: Inhibition Concentration 50%

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

LC50: Lethal concentration 50%

LD50: Lethal Dose 50%

LOAEL: Lowest Observed Adverse Effect Level

LOEL: Lowest observable effect level

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)

MARPOL: Convention for the Prevention of Marine Pollution from Ships

MVZ: molar ratio

n.a.: Not applicable

n.d.: Not determined

n.r.: Not relevant

NLP: No Longer Polymers

NOAEC: No Observed Adverse Effect Concentration

NOAEL: No Observed Adverse Effect Level

NOEC: No Observed Effect Concentration

NOEL: No Observed Effect Level

OEL: Occupational Exposure Limit

PBT: Persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RCP: Reciprocal calculation procedure

REACH: Registration, Evaluation and Authorization of Chemical)

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)

STEL: Short-term Exposure Limit

SVHC: Substance of Very High Concern

TLV - TWA: Threshold Limit Value - Time Weighted Average

VOC: Volatile Organic Compounds

vPvB: Very persistent, very bioaccumulative.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Spray Paint Exhaust 671
Sprühlack Auspuff 671
Revision date : 13.11.2024
Print date : 13.11.2024

Version (Revision) : 19.0.0 (18.0.1)

16.3 Key literature references and sources for data

Regulation (EC) No. 1907/2006 (REACH), amended by the Regulation (EC) 2020/878
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixture
ADN: (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
ADR: (Accord européen relatif transport des marchandises dangereuses par route)
Database of the registered Substances of the European Chemicals Agency (ECHA)
GESTIS - Database on hazardous substances - (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)
Information of our suppliers
GISBAU (Hazardous materials information system of the German professional associations of the building and construction industry)

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.