according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG www.brillux.de

Street: Weseler Straße 401

Postal code/City: D - 48163 Münster

Telephone: +49 (0)251-7188-0 **Telefax:** +49 (0)251-7188-280 **Information contact:**

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):

(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)

Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1; H222 - Aerosols: Category 1; Extremely flammable aerosol.

Aerosol 1; H229 - Aerosols: Category 1; Pressurised container: May burst if heated.

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Flame (GHS02) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

FATTY ACIDS, C14-18 AND C16-18-UNSATD., MALEATED; CAS No.: 85711-46-2

Page: 1 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070

Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

MALEIC ANHYDRIDE; CAS No.: 108-31-6

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

P261 Avoid breathing spray.

P501 Dispose of contents/container to approved disposal company or local collection.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eve irritation persists: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

Adverse physicochemical effects

Caution! Pressurized container.

Without sufficient ventilation formation of explosive mixtures may be possible.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Mixture based on components, which are called following, and other components.

Hazardous ingredients

ETHANOL; REACH No.: 01-2119457610-43; EC No.: 200-578-6; CAS No.: 64-17-5

Weight fraction : \geq 25 - < 50 %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319

Specific Conc. Limits : Eye Irrit. 2 ; H319: $C \ge 50 \%$

PROPANE ; REACH No. : 01-2119486944-21 ; EC No. : 200-827-9; CAS No. : 74-98-6

Weight fraction : $\geq 10 - < 25 \%$

Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280 BUTANE ; REACH No. : 01-2119474691-32 ; EC No. : 203-448-7; CAS No. : 106-97-8

Weight fraction : \geq 10 - < 25 %

Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280 ISOBUTANE ; REACH No. : 01-2119485395-27 ; EC No. : 200-857-2; CAS No. : 75-28-5

Weight fraction : \geq 10 - < 25 %

Classification 1272/2008 [CLP]: Flam. Gas 1; H220 Press. Gas (Liq.); H280

FATTY ACIDS, C14-18 AND C16-18-UNSATD., MALEATED; REACH No.: 01-2119976378-19; EC No.: 288-306-2; CAS No.:

85711-46-2

Page: 2 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070

Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

Weight fraction : $\geq 0,1 - < 1 \%$

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Skin Sens. 1; H317

MALEIC ANHYDRIDE; REACH No.: 01-2119472428-31; EC No.: 203-571-6; CAS No.: 108-31-6

Weight fraction : $\geq 0.001 - < 0.1 \%$

Classification 1272/2008 [CLP]: Resp. Sens. 1; H334 STOT RE 1; H372 Skin Corr. 1B; H314 Eye Dam. 1; H318

Acute Tox. 4; H302 Skin Sens. 1A; H317 EUH071

Specific Conc. Limits : Skin Sens. 1A ; H317: $C \ge 0,001 \%$

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical adivce if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation, eye iriitation and irritation to respiratory tract are possible. Allergic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO2, powders or water spray for extinction. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Can form explosive gas-air mixtures. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if

Page: 3 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070

Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

necessary for the firefighting.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep no protective persons away, personal should wear protective clothings. Refer to protective measures listed in sections 7 and 8. Avoid contact with eyes and skin. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Ensure adequate ventilation. The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8,

information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Keep away from heat and direct sunlight. Ensure a good ventilation in room and working area. Avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit) or other thresholds. Vapours are heavier than air ensure a good ventilation in room and working area. Read label before use.

Measures to prevent fire

Keep ignation sources away - Do not smoke. Container is under pressure. Protect against sunshine and heating over 50 °C. After use: do not open violently or burn. Do not spray into flames or on glowing materials.

Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

Advices on general occupational hygiene

While working do not eat , drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Observe official regulations on storing packagings with pressurized containers. Store in a well-ventilated place. Keep cool. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Do not store the product in lounge room. Keep out of the reach of children.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

Storage class (TRGS 510): 2B

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

Page: 4 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE: This product can not be encoded in accordance with GISBAU.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

ETHANOL; CAS No.: 64-17-5

Limit value type (country of origin): TRGS 900 (D)

 $\label{eq:limit_value:} \mbox{Limit value:} \qquad \qquad \mbox{200 ppm} \ \ / \ \ 380 \ \mbox{mg/m}^3$

Peak limitation: 4(II)
Remark: Y
Version: 23.06.2022

PROPANE; CAS No.: 74-98-6

Limit value type (country of origin) : TRGS 900 (D) $\,$

 $\label{eq:limit_value} \mbox{Limit value}: \qquad \qquad 1000 \mbox{ ppm} \ \ / \ \ 1800 \mbox{ mg/m}^3$

Peak limitation: 4(II)
Version: 23.06.2022

BUTANE; CAS No.: 106-97-8

Limit value type (country of origin): TRGS 900 (D)

Limit value : 1000 ppm / 2400 mg/m³

Peak limitation: 4(II)
Version: 23.06.2022

ISOBUTANE ; CAS No. : 75-28-5

Limit value type (country of origin): TRGS 900 (D)

Limit value : 1000 ppm / 2400 mg/m³

Peak limitation: 4(II)
Version: 23.06.2022

Remark

Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

DNEL-/PNEC-values

DNEL/DMEL

ETHANOL ; CAS No. : 64-17-5

Limit value type : DNEL Consumer (local)

Exposure route: Dermal
Exposure frequency: Short-term
Limit value: 950 mg/kg
Assessment factor: 1 D

Limit value type : DNEL Consumer (local)

Exposure route: Inhalation
Exposure frequency: Short-term
Limit value: 950 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route: Oral
Exposure frequency: Long-term
Limit value: 87 mg/kg
Assessment factor: 1 D

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal Exposure frequency : Long-term

Page: 5 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

Limit value : 206 mg/kg Assessment factor : 1 D

Limit value type : DNEL Consumer (systemic)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 114 mg/m³
Limit value type: DNEL worker (local)

Exposure route: Inhalation
Exposure frequency: Short-term
Limit value: 1900 mg/m³

Limit value type : DNEL worker (systemic)

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 343 mg/kg

Assessment factor: 1 [

Limit value type : DNEL worker (systemic)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 950 mg/m³

PNEC

ETHANOL; CAS No.: 64-17-5

Limit value type: PNEC (Aquatic, freshwater)
Exposure route: Water (Including sewage plant)

Limit value : 0,96 mg/l

Limit value type : PNEC (Aquatic, intermittent release) Exposure route : Water (Including sewage plant)

Limit value : 2,75 mg/l

Limit value type: PNEC (Aquatic, marine water)
Exposure route: Water (Including sewage plant)

Limit value : 0,79 mg/l

Limit value type : PNEC (Sediment, freshwater)

Exposure route : Soil
Limit value : 3,6 mg/kg

Limit value type : PNEC (Sediment, marine water)

Exposure route: Soil
Limit value: 2,9 mg/kg
Assessment factor: 1 D
Limit value type: PNEC soil
Exposure route: Soil
Limit value: 0,63 mg/l

Limit value type: PNEC (Sewage treatment plant)
Exposure route: Water (Including sewage plant)

Limit value: 580 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use safety glasses.

Skin protection

Page: 6 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

Hand protection

At use as agreed a protective gloves from nitrile rubber with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 60 min. By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Using protective clothing.

Respiratory protection

Use suitable respiratory protective device in case of insufficient ventilation. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use the combination filter mask A2 - P3. Do not breathe gas or spray.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe gas or spray.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Aerosol.

Colour: conformable to product designation.

Odour

Smell of organic solvents.

Safety characteristics

Melting point/freezing point: (1013 hPa) No data available Initial boiling point and boiling (1013 hPa) °C -44 range: (1013 hPa) No data available **Decomposition temperature:** °C Flash point : 0 **Auto-ignition temperature:** 365 °C Lower explosion limit: 1,5 Vol-% Upper explosion limit: 15 Vol-% Vapour pressure: (20°C) 3600 hPa Density: (20°C) 0,858 - 0,872 g/cm3 Water solubility: (20°C) Not mixable pH: not applicable log P O/W: No data available Viscosity: (20°C) No data available Kinematic viscosity: (40°C) No data available Weight-% Solid content:

 Solid content :
 18,5 - 19,5
 Weight-%

 Solvent content :
 80,5 - 81
 Weight-%

Relative vapour density : (20 °C) No data available

VOC-value : < 840 g/l

Aerosols : Extremely flammable.

Particle Characterics : not applicable

9.2 Other information

Other physical and chemical data have not been determined.

Page: 7 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

26.09.2023 **Version (Revision) :** 4.0.0 (3.0.0)

Print date : 26.09.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

Revision date:

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter: LD50 (ETHANOL ; CAS No. : 64-17-5)

Exposure route : Oral Species : Rat

Effective dose: 10470 mg/kg

Parameter: LD50 (ETHANOL; CAS No.: 64-17-5)

Exposure route: Oral
Species: Rabbit
Effective dose: 6300 mg/kg

Parameter: LD50 (MALEIC ANHYDRIDE ; CAS No. : 108-31-6)

Exposure route: Oral
Species: Rat
Effective dose: 850 mg/kg

Parameter: LD50 (MALEIC ANHYDRIDE ; CAS No. : 108-31-6)

Exposure route: Oral
Species: Mouse
Effective dose: 60 mg/kg

Acute dermal toxicity

Parameter: LD50 (ETHANOL; CAS No.: 64-17-5)

Exposure route : Dermal
Species : Rabbit
Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : LC50 (ETHANOL ; CAS No. : 64-17-5)

Exposure route: Inhalation

Page: 8 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

Species: Mouse
Effective dose: > 20 mg/l
Exposure time: 4 h

Parameter: LC50 (ISOBUTANE ; CAS No. : 75-28-5)

Exposure route: Inhalation
Species: Rat
Effective dose: 57 pph

Parameter: LC50 (BUTANE; CAS No.: 106-97-8)

Exposure route: Inhalation
Species: Rat
Effective dose: 659 g/m³

Parameter: LC50 (BUTANE; CAS No.: 106-97-8)

Exposure route: Inhalation
Species: Mouse
Effective dose: 680 g/m³

Corrosion

Irritation:

- Skin contact: Frequently or prolonged contact with skin may cause dermal irritation.
- Eye contact: Causes serious eye irritation.

Respiratory or skin sensitisation

The product is labeled as skin sensitizing.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.

Symtoms and signs include headache: dizzines, fatique, muscular weakness, drowsiness and in extreme cases loss of consciouness.

The liquid splached in the eyes may cause irritation and reversible demage.

STOT-repeated exposure

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Aspiration hazard

No risk expected.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regualtion), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Page: 9 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070

Kurzzeit-Markierer 1070

Revision date : 26.09.2023 **Version (Revision) :** 4.0.0 (3.0.0)

Print date : 26.09.2023

Acute (short-term) toxicity to algae and cyanobacteria

Parameter: EC50 (ETHANOL ; CAS No. : 64-17-5)
Species: Daphnia magna (Big water flea)

Effective dose: > 10000 mg/l

Exposure time: 48 h

Parameter: EC50 (ETHANOL; CAS No.: 64-17-5)

Species: Chlorella vulgaris
Effective dose: 275 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

These are not data avaible about the potential of the product concerning his persistency and degradability.

12.3 Bioaccumulative potential

These are not data availble about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas availble about the potential of the product concerning his mobility in the ground.

A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

Avoid exposing into ground, waterways and drainage.

Danger of drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

Waste codes/waste designations according to EWC/AVV

For the product:

Disposal-definition No.: 08 01 11* - Paint and varnish waste which contains organic solvents or other dangerous substances.

After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Disposal-definition No.: 15 01 10* - packaging containing residues of or contaminated by hazardous substances.

SECTION 14: Transport information

14.1 UN number

Page: 10 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070

Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

UN 1950

14.2 UN proper shipping name

Land transport (ADR/RID)

AEROSOLS

Sea transport (IMDG)

AEROSOLS

Air transport (ICAO-TI / IATA-DGR)

AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 2
Classification code: 5F
Hazard identification number (Kemler
No.): 23
Tunnel restriction code: D
Special provisions: LQ 1 | E 0
Hazard label(s): 2.1

Sea transport (IMDG)

 Class(es):
 2.1

 EmS-No.:
 F-D / S-U

 Special provisions:
 LQ 1 | E 0

 Hazard label(s):
 2.1

Hazard label(s): 2.1
Air transport (ICAO-TI / IATA-DGR)

Class(es): 2.1 Hazard label(s): 2.1

14.4 Packing group

_

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the Internationa Maritime Organization (IMO) instruments.

14.8 Additional information

ADR/RID: Limited quantities.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture $^{15.1}$

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

National regulations

Water hazard class

Self-classification - Class: 1 (Slightly hazardous to water)

Page: 11 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070

Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

Additional information

Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report DNEL: Derived No Effect Level EC: European Commission EC50: Effective Concentration 50%

EC50: Effective Concentration 50% ECHA: European Chemical Agency EEC: European Economic Community

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EWC: European Waste Catalogue

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

IATA: International Air Transport Association ICAO: International Civil Aviation Organization IC50: Inhibition Concentration 50%

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

LC50: Lethal concentration 50%

LD50: Lethal Dose 50%

LOAEL: Lowest Observed Adverse Effect Level

LOEL: Lowest observable effect level

MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)

MARPOL: Convention for the Preventation of Marine Pollution from Ships

MVZ: molar ratio n.a.: Not applicable n.d.: Not determined n.r.: Not relevant NLP: No Longer Polymers

NOAEC: No Observed Adverse Effect Concentration

NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration NOEL: No Observed Effect Level OEL: Occupational Exposure Limit PBT: Persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RCP: Reciprocal calculation procedure REACH: Registration, Evaluation and Authorization of Chemical)

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant

Page: 12 / 13

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Non-Permanent Marker 1070 Kurzzeit-Markierer 1070

Revision date: 26.09.2023 **Version (Revision):** 4.0.0 (3.0.0)

Print date : 26.09.2023

le transport de marchandises dangereuses par chemin de fer)

STEL: Short-term Exposure Limit SVHC: Substance of Very High Concern

TLV - TWA: Threshold Limit Value - Time Weighed Average

VOC: Volatile Organic Compounds

vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372 IF INHALED: Causes damage to organs through prolonged or repeated exposure.

EUH071 Corrosive to the respiratory tract.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 13 / 13