

Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

9.0.0 (8.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Hydro-PU-XSpray Isoprimer 2243

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

1.3 Details of the supplier of the safety data sheet

Supplier

Brillux GmbH & Co KG www.brillux.de

Street : Weseler Straße 401

Postal code/City: D - 48163 Münster

Telephone: +49 (0)251-7188-0

Telefax: +49 (0)251-7188-280

Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.): (Giftinformationszentrum-Nord, Göttingen, consultation in german or english language) Telephone: +49 (0)551-19240.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP] None

Additional information

This product is not dangerous according to the regulation (EC) No. 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

 EUH210
 Safety data sheet available on request.

2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description



Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

Primer based on a polymer resin;
Composition:
Cationic polymer resin, titanium dioxide, barium sulphate, silicates, water, glycol ether and additives.Hazardous ingredients
CATIONIC EPOXY-AMINE POLYMER
Weight fraction :
Classification 1272/2008 [CLP] :
Aquatic Chronic 3 ; H412
(2-METHOXYMETHYLETHOXY)PROPANOL ; REACH No. : 01-2119450011-60 ; EC No. : 252-104-2; CAS No. : 34590-94-8
Weight fraction :
 $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] :
Substance with a community workplace exposure limitAdditional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. If unconscious no administration by mouth, storage in recovery position and seek medical advice. If medical advice is needed, have product container or label at hand.

Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration.

In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical adivce if complaint continues.

Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

4.2 Most important symptoms and effects, both acute and delayed Allergic symptoms.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
 - Suitable extinguishing media

This product is not flammable. In case of a fire extingnish surroundings as indicated.

Unsuitable extinguishing media

None known.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

Page : 2 / 10



Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. The product produced in combination with water slippery surfaces.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove residue by rinsing thoroughly with water. Thoroughly clean contaminated objects and floors and observe environmental regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. You find information about the safety equipment of persons in the section 8,

information about the refuse disposal in section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and working area. For personal protection see Section 8. Keep out of reach of children. Read label before use.

Measures to prevent fire

This product is not flammable. Cool endangered containers with water.

Advices on general occupational hygiene

While working do not eat , drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Do not store the product in lounge room. Keep only in the original container. Protect against frost. Keep out of the reach of children.

Hints on joint storage

Store away from foodstuffs.

Storage class (TRGS 510): 12

Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

Industrial sector specific solutions

GISCODE : Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): BSW20

SECTION 8: Exposure controls/personal protection



Trade name : Revision date : Print date :

8.1 Control parameters

Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

Occupational exposure limit values (2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8 Limit value type (country of origin) : TRGS 900 (D) Limit value : 50 ppm / 310 mg/m³ Peak limitation : 1(I) 02.07.2021 Version: Limit value type (country of origin) : TWA (EC) Limit value : 50 ppm / 308 mg/m³ Remark : Skin Version: 20.06.2019 Remark Taking into account the details mentioned in the TRGS 900 for the supervision of AGW. **DNEL-/PNEC-values** DNEL/DMEL (2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8 Limit value type : DNEL Consumer (systemic) Exposure route : Dermal Exposure frequency : Long-term Limit value : 15 mg/kg Assessment factor : 1 D DNEL Consumer (systemic) Limit value type : Exposure route : Inhalation Exposure frequency : Long-term Limit value : 37,2 mg/m³ Limit value type : DNEL Consumer (systemic) Exposure route : Oral Exposure frequency : Long-term Limit value : 1,67 mg/kg Assessment factor : 1 D Limit value type : DNEL worker (systemic) Exposure route : Dermal Long-term Exposure frequency : 65 mg/kg Limit value : Assessment factor : 1 D Limit value type : DNEL worker (systemic) Exposure route : Inhalation Exposure frequency : I ona-term 310 mg/m³ Limit value : PNFC (2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8 Limit value type : PNEC (Aquatic, freshwater) Exposure route : Water (Including sewage plant) Limit value : 19 mg/l Limit value type : PNEC (Aquatic, marine water) Exposure route : Water (Including sewage plant) Limit value : 1,9 mg/l Limit value type : PNEC (Sediment, freshwater) Exposure route : Soil Limit value : 70,2 mg/kg PNEC (Sediment, marine water) Limit value type : Exposure route : Soil Limit value : 7,02 mg/kg PNEC soil Limit value type :



Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

Exposure route : Limit value : Limit value type : Exposure route : Limit value : Soil 2,74 mg/kg PNEC (Sewage treatment plant) Water (Including sewage plant) 4168 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

Personal protection equipment

Eye/face protection

Use protection glasses in case of spattering.

Skin protection

Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

Body protection

If the product must sprayed, use a disposable protective suit.

Respiratory protection

By spraying: Use the combination filter mask A2/P2. Do not breathe spray.

General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe gas or spray.

Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : conformable to product designation.

Odour

Poor, characteristic.

Safety characteristics

Melting point/freezing point :	(1013 hPa)		No data available	
Initial boiling point and boiling range :	(1013 hPa)	>	100	°C
Decomposition temperature :	(1013 hPa)		No data available	
Flash point :			not applicable	
Auto-ignition temperature :			not applicable	
Lower explosion limit :			not applicable	
Upper explosion limit :			not applicable	
Vapour pressure :	(50 °C)		No data available	

Page : 5 / 10



30 g/l

Trade name : Revision date : Print date :	Hydro-P 20.02.2 20.02.2			Version (Rev	ision) :	9.0.0 (8.0.0)
Density : Solvent separatio		(20 °C) (20 °C)	approx.	1,38 - 1,42 not applicable	g/cm ³	
Water solubility : pH : log P O/W :	1	(20 °C)		mixable 5 - 6 No data available		
Flow time : Viscosity :		(20 °C) (20 °C)		No data available thixotropic		DIN-cup 4 mm
Kinematic viscos Relative vapour o	•	(40 °C) (20 °C)		No data available No data available		

max.

9.2 **Other information**

Flammable liquids :

Particle Characterics :

VOC-value :

Other physical and chemical data have not been determined.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

The product is not ignitable.

not applicable

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No dangerous reactions are known if stored and handled the product correctly.

10.4 Conditions to avoid

Keep away from frost, heat and direct sunlight.

10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

- Acute toxicity: - Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

Acute oral toxicity

Parameter :	ATEmix calculated		
Exposure route :	Oral		
Effective dose :	not relevant		
Acute dermal toxicity			
Parameter :	ATEmix calculated		
Exposure route :	Dermal		
Effective dose :	not relevant		
Acute inhalation toxicity			
Parameter :	ATEmix calculated		
Exposure route :	Inhalation (vapour)		
Effective dose :	not relevant		

Page : 6 / 10



Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

Corrosion

- To the skin: Not expecting any damage or irritancy.

- At the eye: Not expecting any damage or irritancy.

Respiratory or skin sensitisation

Contains epoxy constituents. May produce an allergic reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

STOT-single exposure

No risk expected.

STOT-repeated exposure

No risk expected.

Aspiration hazard

No risk expected.

11.2 Information on other hazards

Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regualtion), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

SECTION 12: Ecological information

12.1 Toxicity

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

Aquatic toxicity

Acute (short-term) toxicity to algae and cyanobacteria

Parameter :	EC50 (CATIONIC EPOXY-AMINE POLYMER)			
Species :	Pseudokirchneriella subcapitata			
Evaluation parameter :	Acute (short-term) algae toxicity			
Effective dose :	= 10,4 mg/l			
Exposure time :	72 h			
Chronic (long-term) toxicity to aquatic algae and cyanobacteria				
Parameter :	EC10 (CATIONIC EPOXY-AMINE POLYMER)			
Species :	Pseudokirchneriella subcapitata			
Effective dose :	= 2,32 mg/l			
Exposure time :	72 h			

12.2 Persistence and degradability

These are not data avaible about the potential of the product concerning his persistency and degradability.

12.3 Bioaccumulative potential

These are not data availble about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas available about the potential of the product concerning his mobility in the ground. A penetrating into soil, waters and sewage system should be prevented.

12.5 Results of PBT and vPvB assessment

This product does not contain any relevant substances which were classified as a PBT or vPvB-substance.

Page : 7 / 10



 Trade name :
 Hydro-PU-XSpray Isoprimer 2243

 Revision date :
 20.02.2023

 Print date :
 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains. **Waste codes/waste designations according to EWC/AVV**

For the product:

Disposal-definition No.: 08 01 12 - Paint and varnish waste with the exception of the ones who come under 08 01 11 *.

After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards No dangerous good in sense of these transport regulations.

6 Enocial procestions for usor

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the Internationa Maritime Organization (IMO) instruments.

SECTION 15: Regulatory information

^{15.1} Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Page : 8 / 10



Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions):

Use restriction according to REACH annex XVII, no.: 55, 75

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Product sub-category and VOC limiting values in accordance with appendix II, letter A of the guideline: Category G, type Wb;

VOC limiting value of the category for 2010: 30 g/l.

This product contains max. 30 g/l VOC.

National regulations

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

Additional information

The product is classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils the criteria for solid substances according to the TRwS 779 number 2.1.1. Maternity regulations and Young Persons Employment Act are to take into account.

15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Label elements

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route) AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany) AOX: Adsorbable Organic halogen compounds ATEmix: Calculated acute toxicity estimate of mixture BCF: Bio-Concentration Factor CAS: Chemical Abstract Service CLP: Classification, Labelling and Packaging CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction CSR: Chemical Safety Report DNEL: Derived No Effect Level EC: European Commission EC50: Effective Concentration 50% ECHA: European Chemical Agency EEC: European Economic Community EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances EWC: European Waste Catalogue GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals IATA: International Air Transport Association ICAO: International Civil Aviation Organization IC50: Inhibition Concentration 50% IMDG Code: International Maritime Dangerous Goods Code IMO: International Maritime Organization LC50: Lethal concentration 50% LD50: Lethal Dose 50% LOAEL: Lowest Observed Adverse Effect Level LOEL: Lowest observable effect level MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG) MARPOL: Convention for the Preventation of Marine Pollution from Ships MVZ: molar ratio



Trade name : Revision date : Print date : Hydro-PU-XSpray Isoprimer 2243 20.02.2023 20.02.2023

Version (Revision) :

9.0.0 (8.0.0)

n.a.: Not applicable n.d.: Not determined n.r.: Not relevant NLP: No Longer Polymers NOAEC: No Observed Adverse Effect Concentration NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration NOEL: No Observed Effect Level **OEL:** Occupational Exposure Limit PBT: Persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RCP: Reciprocal calculation procedure REACH: Registration, Evaluation and Authorization of Chemical) RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer) STEL: Short-term Exposure Limit SVHC: Substance of Very High Concern TLV - TWA: Threshold Limit Value - Time Weighed Average VOC: Volatile Organic Compounds vPvB: Very persistent, very bioaccumulative.

16.3 Key literature references and sources for data

None

^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

16.5 Relevant H- and EUH-phrases (Number and full text)

Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

H412

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.