# according to Regulation (EC) No. 1907/2006 (REACH)



Adhesive LF 3064

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Adhesive LF 3064 Haftkleber LF 3064

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

### **Relevant identified uses**

**Products Category [PC]** 

PC 1 - Adhesives, sealants

### Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

# 1.3 Details of the supplier of the safety data sheet

### Supplier

Brillux GmbH & Co KG www.brillux.de

Street: Weseler Straße 401

Postal code/City: D - 48163 Münster

**Telephone:** +49 (0)251-7188-0 **Telefax:** +49 (0)251-7188-280 Information contact:

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

## 1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):

(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)

Telephone: +49 (0)551-19240.

### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 [CLP]

#### Additional information

This product is not dangerous according to the regulation (EC) No. 1272/2008 (CLP).

# 2.2 Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

## Special rules for supplemental label elements for certain mixtures

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE; REACTION MASS OF: 5-CHLORO-2-METHYL-4-**EUH208** 

ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1). May produce an

allergic reaction.

**FUH210** Safety data sheet available on request.

## 2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

# **SECTION 3: Composition/information on ingredients**

Page: 1 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Adhesive LF 3064 Trade name:

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

### 3.2 Mixtures

#### Description

Mixture based on components, which are called following, and other components.

### **Hazardous ingredients**

POLY(OXY-1,2 ETHANEDIYL), ALPHA-SULFO-OMEGA (ISOTRIDECYLOXY)-, SODIUM SALT; CAS No.: 150413-26-6

Weight fraction: ≥ 1 - < 2.5 %

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Eye Irrit. 2; H319

1,2-BENZISOTHIAZOL-3(2H)-ONE; REACH No.: 01-2120761540-60; EC No.: 220-120-9; CAS No.: 2634-33-5

Weight fraction: ≥ 0,025 - < 0,05 %

Classification 1272/2008 [CLP]: Acute Tox. 2; H330 Eye Dam. 1; H318 Acute Tox. 4; H302 Skin Irrit. 2; H315

Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411

Specific Conc. Limits: Skin Sens. 1; H317: C ≥ 0,05 % • (M Acute=1)

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS

No.: 55965-84-9

Weight fraction: ≥ 0.0002 - < 0.0015 %

Acute Tox. 2; H310 Acute Tox. 2; H330 Acute Tox. 3; H301 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1 Classification 1272/2008 [CLP]:

; H410 EUH071

Eye Dam. 1 ; H318: C  $\geq$  0,6 % • Skin Corr. 1C ; H314: C  $\geq$  0,6 % • Eye Irrit. 2 ; Specific Conc. Limits:

H319: C ≥ 0,06 % • Skin Irrit. 2 ; H315: C ≥ 0,06 % • Skin Sens. 1A ; H317: C ≥

0,0015 % • (M=100)

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. If unconscious no administration by mouth, storage in recovery position and seek medical advice. If medical advice is needed, have product container or label at hand.

### Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration.

#### In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

#### After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical adivce if complaint continues.

### Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

## 4.2 Most important symptoms and effects, both acute and delayed

Allergic symptoms.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

Page: 2 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Adhesive LF 3064 Trade name:

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

### 5.1 Extinguishing media

### Suitable extinguishing media

This product is not flammable. In case of a fire extingnish surroundings as indicated.

## Unsuitable extinguishing media

None known.

# 5.2 Special hazards arising from the substance or mixture

### **Hazardous combustion products**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

## 5.3 Advice for firefighters

### Special protective equipment for firefighters

When extinguishing fires, use breathing apparatus with an independent source of air.

### 5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. The product produced in combination with water slippery surfaces

## 6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Remove residue by rinsing thoroughly with water. Thoroughly clean contaminated objects and floors and observe environmental regulations.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

You find information about the safety equipment of persons in the section 8,

information about the refuse disposal in section 13.

## **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

### **Protective measures**

No special measures necessary in the case of regulation storage and handling. Ensure a good ventilation in room and working area. For personal protection see Section 8. Keep out of reach of children. Read label before use.

#### Measures to prevent fire

This product is not flammable. Cool endangered containers with water.

# Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly in a dry, cool and good ventilated place. Do not store the product in lounge room. Keep only in the original container. Protect against frost. Keep out of the reach of children.

## Hints on joint storage

Page: 3 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Adhesive LF 3064

Haftkleber LF 3064

**Revision date:** 22.12.2022 **Version (Revision):** 6.0.0 (5.0.0)

**Print date :** 22.12.2022

Store away from foodstuffs. **Storage class (TRGS 510):** 12

### **Further information on storage conditions**

Keep container tightly sealed. Store at  $5^{\circ}$ - $35^{\circ}$ C. Containers should be kept dry and sealed.

### 7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

### **Industrial sector specific solutions**

**GISCODE:** Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry - GISCODE): D 1.

## **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

### **DNEL-/PNEC-values**

#### **DNEL/DMEL**

1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 1,2 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 345 µg/kg bw/day
Limit value type: DMEL worker (systemic)

 $\begin{array}{lll} \mbox{Exposure route}: & \mbox{Inhalation} \\ \mbox{Exposure frequency}: & \mbox{Long-term} \\ \mbox{Limit value}: & \mbox{6,81 mg/m}^3 \end{array}$ 

Limit value type : DMEL worker (systemic)

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 966 µg/kg bw/day

#### PNEC

1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5

Limit value type : PNEC (Aquatic, freshwater)
Exposure route : Water (Including sewage plant)

Exposure time : Short-term Limit value : 4,03 µg/l

Limit value type : PNEC (Aquatic, intermittent release)
Exposure route : Water (Including sewage plant)

Exposure time : Short-term Limit value : 1,1 µg/l

Limit value type: PNEC (Aquatic, marine water)
Exposure route: Water (Including sewage plant)

Exposure time : Short-term Limit value : 403 ng/L

Limit value type: PNEC (Aquatic, marine water)
Exposure route: Water (Including sewage plant)

Exposure time : Long-term Limit value : Long-term 110 ng/L

Limit value type : PNEC Soil, Freshwater

Exposure route : Soil
Exposure time : Short-term

Page: 4 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Adhesive LF 3064

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

> Limit value: 49,9 µg/kg dry weight

Limit value type : PNEC (Soil) Exposure route: Soil Exposure time: Short-term

Limit value : 3 ma/ka dry weiaht Limit value type : PNEC Soil, Marine water

Exposure route: Short-term Exposure time :

Limit value : 4,99 µg/kg dry weight

Limit value type : PNEC (Sewage treatment plant) Exposure route : Water (Including sewage plant)

Exposure time: Short-term Limit value: 1,03 mg/l

### 8.2 Exposure controls

## Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this shoul be achieved by the use of local exhaust ventilation and good general extraction.

Observe data available of section 7.

### Personal protection equipment

## **Eye/face protection**

Use protection glasses in case of spattering.

### Skin protection

#### Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

## **Body protection**

Using protective clothing.

### Respiratory protection

Breathing protection equipment is not required in adequately ventilated places. Do not inhale the vapour.

# **General information**

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

### **Environmental exposure controls**

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

## **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

## **Appearance**

Physical state: Liquid.

Colour: conformable to product designation.

Odour

Poor, characteristic.

### Safety characteristics

Melting point/freezing point: (1013 hPa) No data available

Page: 5 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



DIN-cup 4 mm

Adhesive LF 3064 Trade name:

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

> Initial boiling point and boiling (1013 hPa) °C 100 range:

**Decomposition temperature:** (1013 hPa) No data available Flash point: not applicable Auto-ignition temperature : not applicable Lower explosion limit : not applicable Upper explosion limit: not applicable (50 °C) Vapour pressure: No data available

Density: (20°C) 0.981 a/cm<sup>3</sup> approx.

Solvent separation test : (20°C) not applicable (20 °C) No data available Water solubility:

pH: 5 - 6

log P O/W: No data available

Flow time: (20°C) No data available Viscosity: (20°C) No data available Kinematic viscosity: (40°C) No data available

Relative vapour density: (20°C) No data available **VOC-value:** 1 a/l max.

Flammable liquids: The product is not ignitable.

**Particle Characterics:** not applicable

#### 9.2 Other information

Other physical and chemical data have not been determined.

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

#### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known if stored and handled the product correctly.

# 10.4 Conditions to avoid

Keep away from frost, heat and direct sunlight.

# 10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 **Acute toxicity**

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

### Acute oral toxicity

LD50 ( 1,2-BENZISOTHIAZOL-3(2H)-ONE ; CAS No. : 2634-33-5 ) Parameter:

Exposure route: Oral Rat Species:

Page: 6 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Adhesive LF 3064

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

> Effective dose: 597 mg/kg

Parameter: LC50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Exposure route: Oral Species: Rat Effective dose: 2200 mg/kg

Acute dermal toxicity

Parameter: LD50 (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Exposure route: Species: Rat

> 2000 mg/kg Effective dose:

Acute inhalation toxicity

Parameter: LC50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Exposure route: Inhalation Species: Rat Effective dose: 5,7 mg/l Exposure time: 4 h

Corrosion

- To the skin: Not expecting any damage or irritancy.
- At the eye: Not expecting any damage or irritancy.

## Respiratory or skin sensitisation

The product contains sensitizing substances, which may produce an allergic reaction (see section 2 and 3).

Skin sensitisation

Parameter: Skin sensitisation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Result: Sensitising. **OECD 429** Method:

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

## **STOT-single exposure**

No risk expected.

# **STOT-repeated exposure**

No risk expected.

### **Aspiration hazard**

No risk expected.

## 11.2 Information on other hazards

# **Endocrine disrupting properties**

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

### Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

## **Additional information**

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regualtion), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

Page: 7 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Adhesive LF 3064 Trade name:

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

### **Aquatic toxicity**

### Acute (short-term) fish toxicity

Parameter: EC50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose: 0,22 mg/l 96 h Exposure time:

#### Chronic (long-term) fish toxicity

Parameter: NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Oncorhynchus mykiss (Rainbow trout) Evaluation parameter: Chronic (long-term) fish toxicity

Effective dose: 0,21 mg/l 28 D Exposure time: Method:

Parameter: NOEC ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose: 0.098 ma/l 28 D Exposure time: Acute (short-term) toxicity to crustacea

EC50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-Parameter:

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Effective dose: 0,1 mg/l Exposure time: 48 h

#### Chronic (long-term) toxicity to aquatic invertebrate

NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5) Parameter:

Daphnia magna (Big water flea) Species: Evaluation parameter: Chronic (long-term) daphnia toxicity

Effective dose: 1,2 mg/l Exposure time: 21 D Method: **OECD 211** 

NOEC ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-Parameter:

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Effective dose: 0,004 mg/l Exposure time: 21 D

## Acute (short-term) toxicity to algae and cyanobacteria

EC50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-Parameter:

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Pseudokirchneriella subcapitata

Effective dose: 0,048 mg/l Exposure time: 72 h

Parameter: EL50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Pseudokirchneriella subcapitata

Effective dose: 0,0012 mg/l Exposure time:

EC50 ( REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-Parameter:

METHYL-2H -ISOTHIAZOL-3-ONE (3:1); CAS No.: 55965-84-9)

Species: Algae

Evaluation parameter: Anabaena flos-aquae

Effective dose: 0,043 mg/l Exposure time: 120 h Toxicity to other aquatic plants/organisms

Parameter: NOEC (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Species: Selenastrum capricornutum

Page: 8 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Adhesive LF 3064

Haftkleber LF 3064

**Revision date :** 22.12.2022 **Version (Revision) :** 6.0.0 (5.0.0)

**Print date :** 22.12.2022

Evaluation parameter: Acute (short-term) algae toxicity

Effective dose: 0,04 mg/l Exposure time: 72 h

Sewage treatment plant

Parameter: EC20 (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Inoculum : Activated sludge

Evaluation parameter : Effects in sewage plants

Effective dose : 3,3 mg/l Exposure time : 3 h

Parameter: EC50 (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Inoculum: Activated sludge
Evaluation parameter: Effects in sewage plants

Effective dose : 13 mg/l Exposure time : 3 h

12.2 Persistence and degradability

These are not data avaible about the potential of the product concerning his persistency and degradability.

**Biodegradation** 

Parameter: Biodegradation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Inoculum: Degree of elimination
Degradation rate: approx. 90 %
Evaluation: Biodegradable.
Method: OECD 302B

Parameter: Biodegradation (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Inoculum: Degree of elimination

Degradation rate : > 70 %

Evaluation : Biodegradable.

Method : OECD 303A

12.3 Bioaccumulative potential

Parameter: Bioconcentration factor (BCF) (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Value : 6,95 Method : 0ECD 305

These are not data availble about the bio accumulation potential of the product.

12.4 Mobility in soil

These are not datas availble about the potential of the product concerning his mobility in the ground.

A penetrating into soil, waters and sewage system should be prevented.

**Adsorption** 

Parameter: Log KOW (1,2-BENZISOTHIAZOL-3(2H)-ONE; CAS No.: 2634-33-5)

Effective dose : 0,7
Evaluation : HPLC method
Method : OECD 117

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expecting.

12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

Page: 9 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Adhesive LF 3064 Trade name:

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

# **Directive 2008/98/EC (Waste Framework Directive)**

#### Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

### Waste codes/waste designations according to EWC/AVV

For the product:

Disposal-definition No.: 08 04 10 - Waste adhesives and sealants other than those mentioned in 08 04 09\*.

#### After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

## **SECTION 14: Transport information**

#### 14.1 UN number

No dangerous good in sense of these transport regulations.

## 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

#### 14.4 Packing group

No dangerous good in sense of these transport regulations.

# 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

# 14.6 Special precautions for user

None

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the Internationa Maritime Organization (IMO) instruments.

## **SECTION 15: Regulatory information**

#### Safety, health and environmental regulations/legislation specific for the substance or 15.1 mixture

## **EU** legislation

#### Other regulations (EU)

### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU quideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

### **National regulations**

#### Water hazard class

Classification according to AwSV - Class: 1 (Slightly hazardous to water)

## Additional information

Maternity regulations and Young Persons Employment Act are to take into account.

# 15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

Page: 10 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Adhesive LF 3064

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

#### **SECTION 16: Other information**

# 16.1 Indication of changes

None

### 16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report DNEL: Derived No Effect Level EC: European Commission

EC50: Effective Concentration 50% ECHA: European Chemical Agency EEC: European Economic Community

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EWC: European Waste Catalogue

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IC50: Inhibition Concentration 50%

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

LC50: Lethal concentration 50% LD50: Lethal Dose 50%

LOAEL: Lowest Observed Adverse Effect Level

LOEL: Lowest observable effect level

MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG) MARPOL: Convention for the Preventation of Marine Pollution from Ships

MVZ: molar ratio n.a.: Not applicable n.d.: Not determined n.r.: Not relevant NLP: No Longer Polymers

NOAEC: No Observed Adverse Effect Concentration

NOAEL: No Observed Adverse Effect Level NOEC: No Observed Effect Concentration

NOEL: No Observed Effect Level OEL: Occupational Exposure Limit PBT: Persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration RCP: Reciprocal calculation procedure

REACH: Registration, Evaluation and Authorization of Chemical)

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant

le transport de marchandises dangereuses par chemin de fer)

STEL: Short-term Exposure Limit SVHC: Substance of Very High Concern

TLV - TWA: Threshold Limit Value - Time Weighed Average

VOC: Volatile Organic Compounds

vPvB: Very persistent, very bioaccumulative.

Page: 11 / 12

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Adhesive LF 3064

Haftkleber LF 3064

Revision date: 22.12.2022 Version (Revision): 6.0.0 (5.0.0)

Print date: 22.12.2022

### 16.3 Key literature references and sources for data

# Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation.

H330 Fatal if inhaled.

Very toxic to aquatic life. H400

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

### 16.6 Training advice

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 12 / 12